



Ford BOALINQ™ Flanged Coupling Adapter

Product Release

06/2025

BOALFCA™ Flanged Coupling Adapter

The BOALFCA flanged adapter can be used to join plain end steel, PVC, PVCO, ductile iron, cast iron, asbestos cement, or HDPE pipe to a flange.

- Available in sizes 4"-12".
- Coated 316 stainless steel nuts and bolts offer superior performance.
- Lightweight carbon steel end rings, flange, and sleeve have e-coat epoxy finish with fusion bonded epoxy top coat to increase impact, abrasion and corrosion protection.
- EPDM gaskets with removable and replaceable inner gasket provide greater range.
- Class D flange per AWWA C207 standard. Others available upon request.
- Allows for 4° of deflection.
- Rated to 260 psi.
- NSF 61 Certified.



Nominal Pipe Size	Catalog Number	Flange Size	Total Range (In.)	Range With Inner Gasket (In.)	Range Without Inner Gasket (In.)
4"	BOALFCA-4-D4	4"	4.25 - 5.63	4.25 - 5.00	4.92 - 5.63
6"	BOALFCA-6-D6	6"	6.42 - 7.68	6.42 - 7.05	7.01 - 7.68
8"	BOALFCA-8-D8	8"	8.54 - 9.84	8.54 - 9.17	9.13 - 9.84
10"	BOALFCA-10-D10	10"	10.70 - 12.00	10.70 - 11.37	11.33 - 12.00
12"	BOALFCA-12-D12	12"	12.40 - 13.66	12.40 - 13.03	12.99 - 13.66

For custom size/class flanges, contact factory.

The Ford Meter Box Company, Inc. 775 Manchester Avenue, P.O. Box 443, Wabash, Indiana, USA 46992-0443
Phone: 260-563-3171 • www.fordmeterbox.com

FBOALFCA