



Blow-off Ball Valves

Product Release

05/2016

Ball Valves for Clearing Lines

Ford's blow-off style ball valves are perfect for maintaining a healthy water main. Typically installed at the end of the pipeline, they can be used to flush sediment, relieve pressure or vent excess air. With a vertical discharge outlet, this valve can accommodate a hose or diffuser to meet your need.



Features

- Vertical inlet and outlet with easy access to tee-head
- 300 psi working pressure
- Available with a variety of inlet and outlet connections
- Composed of waterworks brass compliant with AWWA C800's latest revisions
- Full 360° tee-head rotation

Ordering Information

Catalog Number	Valve Size	Inlet	Outlet	Overall Height	Approx. Wt. Lbs.
BLA28-443-TA-NL	1"	1" Flare Copper	3/4" Male Iron Pipe	4-9/32"	3.0
BLA18-677-TA-NL	1-1/2"	2" Female Iron Pipe	2" Male Iron Pipe	6-1/4"	5.9
BLA28-677-TA-AWT-NL	1-1/2"	2" Flare Copper	2" Male Iron Pipe	9-25/32"	9.3
BLA18-777-TA-NL	2"	2" Female Iron Pipe	2" Male Iron Pipe	6-31/64"	9.3

The Ford Meter Box Co., Inc. 775 Manchester Avenue, P.O. Box 443, Wabash, Indiana, USA 46992-0443
Telephone: 260-563-3171 • FAX: 800-826-3487 • Overseas FAX: 260-563-0167 • www.fordmeterbox.com