

UFR1500-SA

Product Release

11/2024

Uni-Flange® Mechanical Joint Restraint for Steel, HDPE*, and IPS PVC Pipe.

A wedge-style restraint for larger steel pipe is now available from Ford Meter Box. This all-domestic restraint is designed for the dimensions and properties of steel pressure pipe and meets the requirements of BABAA and AIS.



Rated to 250 psi with a 2:1 safety factor not to exceed the pressure rating of the pipe.

Nom. PIPE SIZE	PIPE O.D. (In.)	CATALOG NUMBER	No. of RESTRAINT SEGMENTS	APPROX. WEIGHT (LBS.)
3"	3.50	UFR1500-SA-3-U	2	12
4"	4.50	UFR1500-SA-4-U	2	13
6"	6.63	UFR1500-SA-6-U	3	18
8"	8.63	UFR1500-SA-8-U	4	23
10"	10.75	UFR1500-SA-10-U	8	33
12"	12.75	UFR1500-SA-12-U	8	38
14"	14.00	SEE NOTE		
16"	16.00	UFR1500-SA-16-U	12	76
18"	18.00	UFR1500-SA-18-U	12	94
20"	20.00	UFR1500-SA-20-U	14	109
24"	24.00	UFR1500-SA-24-U	16	153

*Note: Inserts or pipe stiffeners are required when restraints or couplings are installed on HDPE pipe. Sewer applications require NBR (Buna-N) gaskets. Contact factory for details.

Note: For 14" steel pipe only, Ford offers the UFR1500-ST-14.

Note: For imported gland, replace -U with -I.