




# SUBMITTAL INFORMATION

## Ball Valve Curb Stop - (B44-xxx-OR-Q-NL style)



### QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



Stainless Steel Gripper  
Molded Spring Tip Gasket Provides Hydraulic Seal

Solid one piece tee-head and stem

Sturdy stops allow 90° motion and are enclosed and protected

Dual EPDM O-rings in the stem

External Nut Stop

Quick Joint Nut

Inlet

Length

A snap ring locks the stem into the body of the valve

Molded EPDM rubber seat with reinforcing ring supports the ball

Quick Joint Nut

Outlet

Brass ball w/ low-friction coating

Due to design variations related to sizing, items may differ from images above.

VALVE SIZE	INLET SIZE	OUTLET SIZE	LENGTH	APPROX. Wt. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
3/4"	3/4"	3/4"	3-11/16"	2.2	B44-333-OR-Q-NL	
3/4"	1"	3/4"	4"	2.6	B44-343-OR-Q-NL	
3/4"	1"	1"	4-27/32"	3.2	B44-344-OR-Q-NL	
1"	1"	1"	4-5/16"	3.2	B44-444-OR-Q-NL	
1-1/4"	1-1/4"	1-1/4"	6-11/32"	5.6	B44-555-OR-Q-NL	
1-1/2"	1-1/2"	1-1/2"	5-23/32"	6.3	B44-666-OR-Q-NL	
2"	2"	2"	6-9/16"	9.4	B44-777-OR-Q-NL	

**Note:** Ford recommends insert stiffeners when using plastic pipe or tubing.

### FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Valve is non-directional and is watertight with flow in either direction
- Ends are integral or secured with adhesive to prevent unintentional disassembly
- Hole for attaching curb box rod or handle is provided in tee-head
- 300 PSI working pressure
- Valve designed with "open right" feature

**Optional Padlock Wing** for locking valve in closed position. Insert "W" into part number

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
Phone: 260-563-3171 / Fax: 800-826-3487  
Overseas Fax: 260-563-0167  
www.fordmeterbox.com

11/09/23

Submitted By: