

SUBMITTAL INFORMATION





FEMALE IRON PIPE THREAD INLET BY TELESCOPING METER SWIVEL SADDLE NUT OUTLET



VALVE SIZE (IN.)	SERVICE LINE SIZE (IN.)	METER SIZE (IN.)	LENGTH (IN.)	HEIGHT (In.)	APPROX. Wt. Lbs	Part Number	✓ SUBMITTED ITEM(S)
5/8	3/4	5/8 x 3/4 & 3/4	2-15/32 - 2-25/32	1-39/64	1.4	BA13-232W-EXP-SN-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- · Ends are integral or secured with adhesive to prevent unintentional disassembly
- · Hole for attaching handle is provided in tee-head
- 300 PSI working pressure
- · Padlock wing for locking valve in closed position
- · Conforms to AWWA C700 for meter threads
- · Octagonal wrench flats for easy wrench placement

Optional full 360° tee-head rotation. Add "R" to end of part number.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

08/02/24

Submitted	Ву