


SUBMITTAL INFORMATION





GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



Due to design variations related to sizing, items may differ from images above.

VALVE SIZE	INLET SIZE	OUTLET Size	LENGTH (In.)	APPROX. Wt. Lbs	Part Number	✓ SUBMITTED ITEM(S)
3/4"	3/4"	3/4"	4-3/32	2.4	BC44-333SW-G-NL	
1"	1"	1"	4-27/32	3.6	BC44-444SW-G-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Ends are integral or secured with adhesive to prevent unintentional disassembly
- Hole for attaching curb box rod or handle is provided in tee-head

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

12/17/24

Submitted By: