



SUBMITTAL INFORMATION

Angle Ball Flange Meter Valves - (BFA73-777W-AWT-NL style)



PACK JOINT FOR PVC PIPE INLET BY METER FLANGE OUTLET, ASSEMBLED WATERTIGHT



VALVE SIZE	SERVICE LINE SIZE INLET	METER SIZE OUTLET	LENGTH (IN.)	HEIGHT (IN.)	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
2"	2"	2"	2-13/16	5-21/32	13.2	BFA73-777W-AWT-NL	

Note: Ford Pack Joints for PVC are only recommended for Schedule 40 and Schedule 80 pipe.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Padlock Wing for locking valve in closed position
- Hole for attaching handle is provided in the tee head
- 300 PSI working pressure
- Includes EPDM drop-in style meter gasket
- Suitable for customer side shut off (outlet side of meter) up to 300 PSI
- Slotted holes are standard on 2" Flanged Meter Valves, allowing 1-1/2" Flange Meter connection
- Ends are integral or secured with adhesive to prevent unintentional disassembly

Optional: Full 360° tee head rotation. Insert "R" into the part number. Example: BFA73-777WR-AWT-NL

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
 Phone: 260-563-3171 / Fax: 800-826-3487
 Overseas Fax: 260-563-0167
www.fordmeterbox.com

Submitted By: