



SUBMITTAL INFORMATION

Straight Ball Meter Valves - (BL43-232W-3-9-Q-NL style)



5/8" VALVES WITH QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS) BY METER SWIVEL NUT



VALVE SIZE	CTS QUICK JOINT SIZE	METER NUT SIZE	LENGTH (IN.)	APPROX. Wt. LBS	PART NUMBER	✓SUBMITTED ITEM(S)
5/8"	3/4"	5/8"x3/4" & 3/4"	3-29/32	1.8	BL43-232W-3-9-Q-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Valve is non-directional and is watertight with flow in either direction
- Ends are integral or secured with adhesive to prevent unintentional disassembly
- Padlock wing for locking valve in closed position
- Hole for attaching handle is provided in the tee-head
- 300 PSI working pressure
- Meter nut drilled for seal wire

Optional full 360° tee-head rotation. Insert "R" into part number.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

Submitted By: