
SUBMITTAL INFORMATION





FEMALE COPPER THREAD BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)



DESCRIPTION		LENGTH	APPROX.	Part	✓ SUBMITTED
FEMALE COP. THRD	P.J. FOR CTS	(ln.)	Wt. Lbs	Number	ITEM(S)
*5/8"	3/4"	1-9/16	.7	C04-23-NL	
3/4"	3/4"	1-13/16	.7	C04-33-NL	
3/4"	1"	2	.8	C04-34-NL	
1"	3/4"	2-1/16	1.0	C04-43-NL	
1"	1"	1-15/16	1.0	C04-44-NL	
1"	1-1/4"	2-3/16	1.4	C04-45-NL	
1-1/4"	1"	2-1/16	1.0	C04-54-NL	
1-1/4"	1-1/4"	2-1/16	1.6	C04-55-NL	
1-1/2"	1-1/2"	3-1/4	2.5	C04-66-NL	
2"	2"	3-7/16	4.5	C04-77-NL	

Note: Ford recommends insert stiffeners when using plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Sleeve design provides octagonal wrench flats for proper installation

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

	Ш	
9/16/25		

^{*} Copper gaskets neither supplied nor required for 5/8" size