

# SUBMITTAL INFORMATION

## Lok-Pak Meter Coupling - (CT34-xx-NL style)



#### CONNECTION FOR TAPPED METER BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)



DESCRIPTION		Levery	APPROX.	Part	✓ SUBMITTED
METER SIZE	PJ FOR CTS	LENGTH	Wt. Lbs	Number	ITEM(S)
1-1/2"	1-1/2"	3-1/4"	2.1	CT34-66-NL	
2"	2"	3-3/4"	2.9	CT34-77-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

#### **FEATURES**

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Flat rubber ring meter gaskets (EPDM) are included with all 1-1/2" and 2" couplings for tapped meters
- Body design provides wrench lugs to facilitate installation

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



### The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

)443			
10/12/16			