



SUBMITTAL INFORMATION

Corporation Stops - (F1102-x-P-NL style)



MALE IRON PIPE THREAD INLET BY PACK JOINT FOR PVC PIPE OUTLET

COPPER PITORIFICE ON INLET



| VALVE SIZE | INLET SIZE | OUTLET SIZE | VALVE LENGTH (IN.) | BODY OUTLET THREADS | APPROX. WT. LBS | PART NUMBER | ✓ SUBMITTED ITEM(S) |
|------------|------------|-------------|--------------------|---------------------|-----------------|---------------|---------------------|
| 3/4" | 3/4" | 3/4" | 3-7/8 | 1" Flare Copper | 1.9 | F1102-3-P-NL | |
| 3/4" | 3/4" | 1" | 4-1/4 | 1-1/4" Flare Copper | 2.5 | F1102-34-P-NL | |
| 1" | 1" | 1" | 4-5/8 | 1-1/4" Flare Copper | 3.1 | F1102-4-P-NL | |

Note: Ford Pack Joints for PVC are only recommended for Schedule 40 and Schedule 80 Pipe.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Body design provides larger, more rugged wrench flats for proper installation
- Meets 100 PSI working pressure requirement of AWWA Standard C800

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
 Phone: 260-563-3171 / Fax: 800-826-3487
 Overseas Fax: 260-563-0167
www.fordmeterbox.com

Submitted By:

09/08/25