



SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve - (FAST-xxx-xA-U style)



STAINLESS STEEL TAPPING SLEEVE WITH CARBON STEEL FLANGE



NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	CATALOG NUMBER**	**FLANGE SIZE	NOMINAL DIMENSIONS - INCHES				MIN. NUMBER OF STUDS	STUD DIA.	APPROX. WT. LBS.	✓ SUBMITTED ITEM(S)
				COUNTER-BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH				
				A	B	C	D				
3"	3.50-3.96	FAST-396-xA-U	2	3-1/16	3-1/4	5-3/8	15	8	5/8"	25	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8"	26	
4"	4.50-4.80	FAST-480-xA-U	2	3-1/16	3-1/4	5-3/8	15	8	5/8"	27	
	4.80-5.10	FAST-510-xA-U	3	4-1/16	3-1/4	4-15/16	15	8	5/8"	28	
	5.05-5.30	FAST-530-xA-U	4	5-1/16	4-1/4	4-15/16	15	8	5/8"	20	
			2	3-1/16	3-1/4	5-3/8	15	8	5/8"	32	
6"	6.60-7.00	FAST-700-xA-U	3	4-1/16	3-1/4	4-15/16	15	8	5/8"	33	
	6.90-7.30	FAST-730-xA-U	4	5-1/16	4-1/4	4-15/16	15	8	5/8"	34	
	7.10-7.50	FAST-750-xA-U	6	7-1/16	6-13/32	5-1/4	15	8	5/8"	38	
			2	3-1/16	3-1/4	5-3/8	15	8	5/8"	37	
8"	8.63-9.05	FAST-905-xA-U	3	4-1/16	3-1/4	4-15/16	15	8	5/8"	38	
	9.05-9.45	FAST-945-xA-U	4	5-1/16	4-1/4	4-15/16	15	8	5/8"	39	
	9.30-9.70	FAST-970-xA-U	6	7-1/16	6-13/32	5-1/4	15	8	5/8"	42	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8"	58	
10"			2	3-1/16	3-1/4	5-3/8	15	8	5/8"	39	
	10.75-11.15	FAST-1115-xA-U	3	4-1/16	3-1/4	4-15/16	15	8	5/8"	40	
	11.05-11.45	FAST-1145-xA-U	4	5-1/16	4-1/4	4-15/16	15	8	5/8"	41	
	11.75-12.15	FAST-1215-xA-U	6	7-1/16	6-13/32	5-1/4	15	8	5/8"	45	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8"	65	
			10	11-1/16	10-15/32	5-7/8	20	12	5/8"	85	
12"			2	3-1/16	3-1/4	5-3/8	15	8	5/8"	42	
	12.75-13.20	FAST-1320-xA-U	3	4-1/16	3-1/4	4-15/16	15	8	5/8"	43	
	13.10-13.50	FAST-1350-xA-U	4	5-1/16	4-1/4	4-15/16	15	8	5/8"	44	
	14.00-14.40	FAST-1440-xA-U	6	7-1/16	6-13/32	5-1/4	15	8	5/8"	48	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8"	68	
			10	11-1/16	10-15/32	5-7/8	20	12	5/8"	88	
14"			12	13-1/16	12-13/32	6	24	14	5/8"	116	
			2	3-1/16	3-1/4	5-3/8	16	10	5/8"	64	
	15.30-15.70	FAST-1570-xA-U	3	4-1/16	3-1/4	4-15/16	16	10	5/8"	65	
	15.80-16.20	FAST-1620-xA-U	4	5-1/16	4-1/4	4-15/16	16	10	5/8"	66	
	16.48-16.88	FAST-1688-xA-U	6	7-1/16	6-13/32	5-1/4	16	10	5/8"	71	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8"	88	
			10	11-1/16	10-15/32	5-7/8	20	12	5/8"	96	
			12	13-1/16	12-13/32	6	24	14	5/8"	125	

Highlighted ranges are recommended for ductile iron pipe and C900/C905 applications.

** To order: Add flanged outlet size to catalog number. Example: The complete FAST catalog number for an 8" pipe (9.05 O.D.) with a 6" carbon steel flange is FAST-905-6A-U.

FEATURES

- Body, straps and UNC threaded studs are made of type 304 stainless steel. Flange is ASTM A36 carbon steel
- All sleeves are fully passivated for corrosion resistance
- 3"-12" rated to 250 psi, 14" rated to 200 psi. Rating not to exceed the pressure rating of the pipe.
- Outlet gasket is NBR (Buna-N) rubber per ASTM D2000
- Certified to ANSI/NSF Standard 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

09/09/22

Submitted By: