


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve - (FAST-xxxx-x-Q style)




STAINLESS STEEL TAPPING SLEEVE

Flange - Type 316 stainless steel with recess per MSS SP-60 to accept standard tapping valves. Flange conforms to AWWA C228 Class D ANSI 150# drilling. Optional carbon steel flange, per AWWA C207, is available.

Lifter bar - Type 316 stainless steel provides a heavy bearing surface for nuts.


Studs, nuts, & washers - Type 316 stainless steel per ASTM A193 and A194. Nuts and washers are coated to prevent galling.

Outlet Pipe - Type 316 stainless steel



3/4-14 No-Lead Brass Test Plug

Armors - Heavy gauge Type 316 stainless steel are vulcanized to gasket to bridge the gap between lugs.



Outlet Gasket - Virgin NBR (Buna-N) compounded for water service, per ASTM D2000. Outlet gasket assures complete seal of outlet area.

Body & Strap - Type 316, stainless steel all welds are fully passivated to restore stainless characteristics.

Full Gasket - Gridded Virgin SBR compounded for water service, per ASTM D2000. Full gasket gives 360° pipe coverage.

NOM. PIPE SIZE (IN.)	SLEEVE O.D. RANGE (IN.)	CATALOG NUMBER**	FLANGE SIZE (IN.)	NOMINAL DIMENSIONS - INCHES				MIN. NUMBER OF STUDS	STUD DIA. (IN.)	APPROX. WT. LBS.	✓ SUBMITTED ITEM(S)
				COUNTER-BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH				
				A	B	C	D				
16	17.30 - 17.70	FAST-1770-x-Q	2	3-1/16	3-1/4	5-3/8	16	15	5/8	73	
	17.40 - 17.80	FAST-1780-x-Q	3	4-1/16	3-1/4	4-15/16	16	15	5/8	74	
	17.75 - 18.15	FAST-1815-x-Q	4	5-1/16	4-1/4	4-15/16	16	15	5/8	75	
	18.15 - 18.62	FAST-1862-x-Q	6	7-1/16	6-13/32	5-1/4	16	15	5/8	78	
	18.60 - 19.00	FAST-1900-x-Q	8	9-1/16	8-13/32	5-3/8	20	14	5/8	100	
	18.80 - 19.20	FAST-1920-x-Q	10	11-1/16	10-15/32	5-7/8	20	14	5/8	114	
			12	13-1/16	12-13/32	6	24	16	5/8	146	
18	19.30 - 19.70	FAST-1970-x-Q	2	3-1/16	3-1/4	5-3/8	16	15	5/8	79	
	19.50 - 19.92	FAST-1992-x-Q	3	4-1/16	3-1/4	4-15/16	16	15	5/8	80	
	19.80 - 20.20	FAST-2020-x-Q	4	5-1/16	4-1/4	4-15/16	16	15	5/8	81	
			6	7-1/16	6-13/32	5-1/4	16	15	5/8	86	
			8	9-1/16	8-13/32	5-3/8	20	14	5/8	106	
			10	11-1/16	10-15/32	5-7/8	20	14	5/8	119	
			12	13-1/16	12-13/32	6	24	16	5/8	153	
20	20.20 - 20.60	FAST-2060-x-Q	2	3-1/16	3-1/4	5-3/8	16	15	5/8	85	
	20.90 - 21.30	FAST-2130-x-Q	3	4-1/16	3-1/4	4-15/16	16	15	5/8	86	
	21.20 - 21.60	FAST-2160-x-Q	4	5-1/16	4-1/4	4-15/16	16	15	5/8	87	
	21.40 - 21.80	FAST-2180-x-Q	6	7-1/16	6-13/32	5-1/4	16	15	5/8	92	
	21.86 - 22.26	FAST-2226-x-Q	8	9-1/16	8-13/32	5-3/8	20	14	5/8	114	
	22.30 - 22.70	FAST-2270-x-Q	10	11-1/16	10-15/32	5-7/8	20	14	5/8	124	
	23.40 - 23.80	FAST-2380-x-Q	12	13-1/16	12-13/32	6	24	16	5/8	159	
24	23.80-24.20	FAST-2420-x-Q	2	3-1/16	3-1/4	5-3/8	16	15	5/8	97	
	25.00-25.40	FAST-2540-x-Q	3	4-1/16	3-1/4	4-15/16	16	15	5/8	98	
	25.60-26.00	FAST-2600-x-Q	4	5-1/16	4-1/4	4-15/16	16	15	5/8	99	
			6	7-1/16	6-13/32	5-1/4	16	15	5/8	103	
			8	9-1/16	8-13/32	5-3/8	20	14	5/8	127	
			10	11-1/16	10-15/32	5-7/8	20	14	5/8	135	
			12	13-1/16	12-13/32	6	24	16	5/8	171	

Highlighted ranges are recommended for ductile iron pipe and C905 PVC applications.

** To order: Add flanged outlet size to catalog number. Example: The complete FAST catalog number for an 20" pipe (21.60 O.D.) with a 12" stainless steel flange is FAST-2160-12-Q. For a carbon steel flange, add "A" to the catalog number. Example: FAST-2160-12A-Q

FEATURES

- Body, straps and UNC threaded studs are made of type 316 stainless steel
- Flange can be either type 316 stainless steel or ASTM A36 carbon steel
- All sleeves are fully passivated for corrosion resistance
- Outlet gasket is NBR (Buna-N) rubber per ASTM D2000
- Certified to ANSI/NSF Standard 61
- 16" rated to 200 psi, 18"-20" rated to 175 psi, 24" rated to 150 psi. Ratings not to exceed the pressure rating of the pipe.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

12/05/24

Submitted By: