

SUBMITTAL INFORMATION





AWWA/CC TAPER THREAD INLET BY FEMALE IRON PIPE OUTLET



Due to design variations related to sizing, items may affect from images above.									
VALVE	INLET	OUTLET SIZE	VALVE	BODY OUTLET	APPROX.	PART	✓ SUBMITTED		
SIZE	SIZE		LENGTH	THREADS	Wt. Lbs.	Number	ITEM(S)		
3/4"	3/4"	3/4"	3-17/32"	3/4" FIP	1.5	FB1600-3-NL			
3/4"	3/4"	1"	3-51/64"	1" FIP	1.7	FB1600-34-NL			
1"	1"	1"	3-49/64"	1" FIP	2.3	FB1600-4-NL			
1-1/4"	1-1/4"	1-1/4"	4-1/2"	1-1/4" FIP	3.2	FB1600-5-NL			
1-1/2"	1-1/2"	1-1/2"	5-3/32"	1-1/2" FIP	4.3	FB1600-6-NL			
1-1/2"	1-1/2"	2"	5-11/32"	2" FIP	4.4	FB1600-67-NL			
2"	2"	2"	5-7/8"	2" FIP	6.8	FB1600-7-NL			
2"	2"	2-1/2"	6-3/8"	2-1/2" FIP	7.5	FB1600-78-NL			

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Ends are integral or secured with adhesive to prevent unintentional disassembly
- 300 PSI working pressure

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

08/03/21

	nitte	