



SUBMITTAL INFORMATION

Fabricated Transition Coupling - (FC23-xxx-xxx-xxB-U100 style)



6" - COUPLINGS FOR JOINING PLAIN END PIPES WITH DIFFERENT O.D.'S WITH EPOXY COATING, TYPE 304 STAINLESS STEEL HARDWARE AND EPDM GASKET



NOM. PIPE SIZE	GASKET RANGE (IN.)		CENTER SLEEVE		BOLTS			OAD	APPROX. WT. LBS.	CATALOG NUMBER	SUBMITTED ITEM(S)
	1ST END	2ND END	APPROX. LENGTH	OAL	No.	DIA.	LENGTH				
6"	6.00	6.00	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-600-600-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-600-600-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-600-600-10B-U100	
			16"	17-1/8"			20"		49	FC23-600-600-16B-U100	
		6.63	5"	6-1/8"			9"		24	FC23-600-663-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-600-663-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-600-663-10B-U100	
			16"	17-1/8"			20"		49	FC23-600-663-16B-U100	
		6.90-7.20	5"	6-1/8"			9"		24	FC23-600-720-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-600-720-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-600-720-10B-U100	
			16"	17-1/8"			20"		49	FC23-600-720-16B-U100	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-600-756-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-600-756-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-600-756-10B-U100	
			16"	17-1/8"			20"		49	FC23-600-756-16B-U100	
	6.63	6.63	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-663-663-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-663-663-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-663-663-10B-U100	
			16"	17-1/8"			20"		49	FC23-663-663-16B-U100	
		6.90-7.20	5"	6-1/8"			9"		24	FC23-663-720-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-663-720-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-663-720-10B-U100	
			16"	17-1/8"			20"		49	FC23-663-720-16B-U100	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-663-756-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-663-756-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-663-756-10B-U100	
			16"	17-1/8"			20"		49	FC23-663-756-16B-U100	
	6.90-7.20	6.90-7.20	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-720-720-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-720-720-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-720-720-10B-U100	
			16"	17-1/8"			20"		49	FC23-720-720-16B-U100	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-720-756-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-720-756-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-720-756-10B-U100	
			16"	17-1/8"			20"		49	FC23-720-756-16B-U100	
	7.21-7.56	7.21-7.56	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-756-756-05B-U100	
			7"	8-1/8"			10-1/2"		29	FC23-756-756-07B-U100	
			10"	11-1/8"			13-1/2"		39	FC23-756-756-10B-U100	
			16"	17-1/8"			20"		49	FC23-756-756-16B-U100	

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Sleeve - ASTM A36 Carbon Steel
- End Ring - Ductile Iron per ASTM A536. Color coded to match gasket
- Gasket - Molded EPDM rubber per ASTM D2000. Embossed with size and end ring color code.
- Bolts & Nuts - Type 304 stainless steel per ASTM A193 and A194
- Finish - Fusion bonded epoxy coating
- 200 PSI rated working pressure
- Certified to NSF/ANSI 61
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

05/02/23

Submitted By: