



SUBMITTAL INFORMATION

Fabricated Transition Coupling - (FC23-xxx-xxx-xxT-U100 style)



4" - COUPLINGS FOR JOINING PLAIN END PIPES WITH DIFFERENT O.D.'S



NOM. PIPE SIZE	GASKET RANGE (IN.)		CENTER SLEEVE LENGTH	APPROX. OAL	BOLTS			OAD	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
	1ST END	2ND END			No.	DIA.	LENGTH				
4"	4.00	4.00	5"	6-1/8"	3	5/8"	9"	8-7/8"	19	FC23-400-400-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-400-400-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-400-400-10T-U100	
		4.50	5"	6-1/8"			9"		19	FC23-400-450-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-400-450-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-400-450-10T-U100	
		4.80-5.14	5"	6-1/8"			9"		19	FC23-400-514-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-400-514-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-400-514-10T-U100	
			5"	6-1/8"			9"		19	FC23-400-557-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-400-557-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-400-557-10T-U100	
		5.15-5.57	5"	6-1/8"			9"	8-7/8"	19	FC23-450-450-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-450-450-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-450-450-10T-U100	
			5"	6-1/8"			9"		19	FC23-450-514-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-450-514-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-450-514-10T-U100	
	4.50	4.50	5"	6-1/8"	3	5/8"	9"		19	FC23-450-557-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-450-557-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-450-557-10T-U100	
		4.80-5.14	5"	6-1/8"			9"		19	FC23-514-514-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-514-514-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-514-514-10T-U100	
		5.15-5.57	5"	6-1/8"			9"		19	FC23-514-557-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-514-557-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-514-557-10T-U100	
		5.15-5.57	5"	6-1/8"	3	5/8"	9"	8-7/8"	19	FC23-557-557-05T-U100	
			7"	8-1/8"			10-1/2"		23	FC23-557-557-07T-U100	
			10"	11-1/8"			13-1/2"		30	FC23-557-557-10T-U100	

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Sleeve - ASTM A36 carbon steel
- End Ring - Ductile Iron per ASTM A536. Color coded to match gasket
- Gasket - NBR (Buna-N) Molded Rubber: embossed with size and end ring color code.
- Bolts & Nuts - Type 316 stainless steel per ASTM A193 and A194
- Finish - Fusion bonded epoxy
- 200 PSI rated working pressure
- Certified to ANSI/NSF61
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

06/01/23

Submitted By: