



SUBMITTAL INFORMATION

Fabricated Transition Coupling - (FC23-xxx-xxx-xxY style)



6" - COUPLINGS FOR JOINING PLAIN END PIPES WITH DIFFERENT O.D.'S WITH EPOXY COATING AND 304 STAINLESS STEEL HARDWARE



NOM. PIPE SIZE	GASKET RANGE		CENTER SLEEVE		BOLTS			OAL	APPROX. WT. LBS.	CATALOG NUMBER	SUBMITTED ITEM(S)
	1ST END	2ND END	APPROX. LENGTH	OAL	No.	DIA.	LENGTH				
6"	6.00	6.00	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-600-600-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-600-600-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-600-600-10Y	
			16"	17-1/8"			20"		49	FC23-600-600-16Y	
		6.63	5"	6-1/8"			9"		24	FC23-600-663-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-600-663-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-600-663-10Y	
			16"	17-1/8"			20"		49	FC23-600-663-16Y	
		6.90-7.20	5"	6-1/8"			9"		24	FC23-600-720-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-600-720-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-600-720-10Y	
			16"	17-1/8"			20"		49	FC23-600-720-16Y	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-600-756-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-600-756-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-600-756-10Y	
			16"	17-1/8"			20"		49	FC23-600-756-16Y	
	6.63	6.63	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-663-663-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-663-663-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-663-663-10Y	
			16"	17-1/8"			20"		49	FC23-663-663-16Y	
		6.90-7.20	5"	6-1/8"			9"		24	FC23-663-720-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-663-720-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-663-720-10Y	
			16"	17-1/8"			20"		49	FC23-663-720-16Y	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-663-756-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-663-756-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-663-756-10Y	
			16"	17-1/8"			20"		49	FC23-663-756-16Y	
	6.90-7.20	6.90-7.20	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-720-720-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-720-720-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-720-720-10Y	
			16"	17-1/8"			20"		49	FC23-720-720-16Y	
		7.21-7.56	5"	6-1/8"			9"		24	FC23-720-756-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-720-756-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-720-756-10Y	
			16"	17-1/8"			20"		49	FC23-720-756-16Y	
	7.21-7.56	7.21-7.56	5"	6-1/8"	4	5/8"	9"	10-15/16"	24	FC23-756-756-05Y	
			7"	8-1/8"			10-1/2"		29	FC23-756-756-07Y	
			10"	11-1/8"			13-1/2"		39	FC23-756-756-10Y	
			16"	17-1/8"			20"		49	FC23-756-756-16Y	

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Sleeve: ASTM A36 Carbon Steel
- End Ring: Ductile Iron per ASTM A536. Color coded to match gasket
- Gasket: SBR Molded Rubber: embossed with size and end ring color code. Optional Buna-N or EPDM
- Bolts & Nuts: 18-8 Type 304 Stainless Steel
- Finish: Epoxy coated per AWWA C213
- 200 PSI - Rated working pressure
- NSF61: NSF 61 Approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

07/29/15

Submitted By: