



SUBMITTAL INFORMATION

Fabricated Transition Coupling - (FC23-xxxx-xxxx-xxR style)



12" - COUPLINGS FOR JOINING PLAIN END PIPES WITH DIFFERENT O.D.'S



NOM. PIPE SIZE	GASKET RANGE		CENTER SLEEVE		BOLTS			OAL	APPROX. WT. LBS.	CATALOG NUMBER	SUBMITTED ITEM(S)
	1ST END	2ND END	LENGTH	APPROX. OAL	No.	DIA.	LENGTH				
12"	12.75	12.75	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1275-1275-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1275-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1275-10R	
		13.20-13.50	5"	6-1/8"			9"		41	FC23-1275-1350-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1350-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1350-10R	
		13.69-14.04	5"	6-1/8"			9"		41	FC23-1275-1404-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1404-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1404-10R	
		14.03-14.38	5"	6-1/8"			9"		41	FC23-1275-1438-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1438-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1438-10R	
	13.20-13.50	13.20-13.50	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1350-1350-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1350-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1350-1350-10R	
		13.69-14.04	5"	6-1/8"			9"		41	FC23-1350-1404-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1404-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1350-1404-10R	
		14.03-14.38	5"	6-1/8"			9"		41	FC23-1350-1438-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1438-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1350-1438-10R	
	13.69-14.04	13.69-14.04	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1404-1404-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1404-1404-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1404-1404-10R	
		14.03-14.38	5"	6-1/8"			9"		41	FC23-1404-1438-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1404-1438-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1404-1438-10R	
	14.03-14.38	14.03-14.38	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1438-1438-05R	
			7"	8-1/8"			10-1/2"		49	FC23-1438-1438-07R	
			10"	11-1/8"			13-1/2"		64	FC23-1438-1438-10R	

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Sleeve: ASTM A36 Carbon Steel
- End Ring: Ductile Iron per ASTM A536. Color coded to match gasket.
- Gasket: SBR Molded Rubber: embossed with size and end ring color code. Optional NBR (Buna-N) or EPDM
- Bolts & Nuts: High Strength Low Alloy Steel per ASTM A242 & AWWA C111. Optional: Types 304 & 316 Stainless or Electro Galvanized.
- Finish: Black Shop Coat with color coded end rings. Optional Fusion Bonded Epoxy.
- 200 PSI - Rated working pressure
- NSF61: NSF 61 Approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

11/28/18

Submitted By: