



SUBMITTAL INFORMATION

Fabricated Transition Coupling - (FC23-xxxx-xxxx-xxT-U100 style)



12" - COUPLINGS FOR JOINING PLAIN END PIPES WITH DIFFERENT O.D.'S WITH EPOXY COATING, NBR (BUNA-N) GASKET AND 316 STAINLESS STEEL HARDWARE



NOM. PIPE SIZE	GASKET RANGE		CENTER SLEEVE		BOLTS			OAD	APPROX. Wt. Lbs.	CATALOG NUMBER	SUBMITTED ITEM(s)
	1ST END (IN.)	2ND END (IN.)	LENGTH	APPROX. OAL	No.	DIA.	LENGTH				
12"	12.75	12.75	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1275-1275-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1275-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1275-10T-U100	
		13.20-13.50	5"	6-1/8"			9"		41	FC23-1275-1350-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1350-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1350-10T-U100	
		13.69-14.04	5"	6-1/8"			9"		41	FC23-1275-1404-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1404-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1404-10T-U100	
		14.03-14.38	5"	6-1/8"			9"		41	FC23-1275-1438-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1275-1438-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1275-1438-10T-U100	
	13.20-13.50	13.20-13.50	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1350-1350-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1350-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1350-1350-10T-U100	
		13.69-14.04	12"	13-1/8"			15-1/2"		73	FC23-1350-1350-12T-U100	
			5"	6-1/8"			9"		41	FC23-1350-1404-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1404-07T-U100	
		14.03-14.38	10"	11-1/8"			13-1/2"		64	FC23-1350-1404-10T-U100	
			5"	6-1/8"			9"		41	FC23-1350-1438-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1350-1438-07T-U100	
		14.03-14.38	10"	11-1/8"			13-1/2"		64	FC23-1350-1438-10T-U100	
		13.69-14.04	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1404-1404-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1404-1404-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1404-1404-10T-U100	
	13.69-14.04	13.69-14.04	5"	6-1/8"			9"		41	FC23-1404-1438-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1404-1438-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1404-1438-10T-U100	
		14.03-14.38	5"	6-1/8"			9"		41	FC23-1438-1438-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1438-1438-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1438-1438-10T-U100	
	14.03-14.38	14.03-14.38	5"	6-1/8"	7	5/8"	9"	18"	41	FC23-1438-1438-05T-U100	
			7"	8-1/8"			10-1/2"		49	FC23-1438-1438-07T-U100	
			10"	11-1/8"			13-1/2"		64	FC23-1438-1438-10T-U100	

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Sleeve - ASTM A36 carbon steel
- End Ring - Ductile iron per ASTM A536. Color coded to match gasket
- Gasket - NBR (Buna-N) Molded Rubber: embossed with size and end ring color code.
- Bolts & Nuts - Type 316 stainless steel per ASTM A193 and A194
- Finish - Epoxy coated per AWWA C213
- 200 PSI - Rated working pressure
- Certified to ANSI/NSF 61
- 100% Manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

10/24/22

Submitted By: