



# SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-1050-1140-Z style)



10" STYLE FC2A COUPLINGS FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S  
WITH EPOXY COATING AND 316 STAINLESS STEEL HARDWARE



NOM. PIPE SIZE	GASKET RANGE 1ST HALF CAT. # (IN.)	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. # (IN.)	END RING COLOR	CENTER SLEEVE		BOLTS			APPROX. OVERALL LGTH.	OAD	APPROX. Wt. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
						LGTH.	APPROX. (THICKNESS)	DIA.	LGTH.	QTY.					
10"	10.50	Red	<input checked="" type="checkbox"/>	11.10-11.40	Blk	6"	7/16"	5/8"	9"	6	7-1/8"	15-11/16"	48	FC2A-1050-1140-Z	

Note: Flexible Couplings do not restrain axial forces on piping.

## FEATURES

- Center Sleeve: Ductile iron per ASTM A536 (65-45-12)
- End Rings: Ductile iron per ASTM A536 (65-45-12)
- Bolts and Nuts: Type 316 stainless steel per ASTM A193 and A194
- Coating: Fusion-bonded epoxy. Applied per AWWA C213
- NSF61: NSF 61 approved
- Gasket: Molded SBR rubber per ASTM D2000
- Complies with AWWA C219

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
Phone: 260-563-3171 / Fax: 800-826-3487  
Overseas Fax: 260-563-0167  
[www.fordmeterbox.com](http://www.fordmeterbox.com)

Submitted By:

06/24/20