



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxx-xxx-P style)



**FC2A COUPLING FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S
WITH 304 STAINLESS STEEL HARDWARE, EPOXY COATING AND NBR (BUNA-N) GASKETS**



NOM. PIPE SIZE	GASKET RANGE 1ST HALF CAT. # (IN.)	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. # (IN.)	END RING COLOR	CENTER SLEEVE		BOLTS			APPROX. OVERALL LGTH.	OAD	APPROX. WT. LBS.	CATALOG NUMBER	✓SUBMITTED ITEM(S)
						LGTH.	APPROX. (T) THICKNESS	DIA.	LGTH.	QTY.					
3"	3.13	Red		3.13	Red	4"	3/8"	5/8"	6-1/2"	3	5-1/8"	6-15/16"	14	FC2A-313-313-P	
	3.45 - 3.60	Red		3.45 - 3.60	Red									FC2A-360-360-P	
	3.70 - 3.88	Blk		3.70 - 3.88	Blk									FC2A-388-388-P	
	3.91 - 4.06	Blk		3.91 - 4.06	Blk									FC2A-406-406-P	
	4.07 - 4.20	Blk		4.07 - 4.20	Blk									FC2A-420-420-P	
4"	4.00	Red		4.00	Red	5"	3/8"	5/8"	8"	3	6-1/8"	8-7/8"	16	FC2A-400-400-P	
	4.00	Red		4.50	Red									FC2A-400-450-P	
	4.00	Red		4.80 - 5.14	Blk									FC2A-400-514-P	
	4.50	Red		4.50	Red									FC2A-450-450-P	
	4.50	Red		4.80 - 5.14	Blk									FC2A-450-514-P	
	4.50	Red		5.15 - 5.57	Wht/Gry									FC2A-450-557-P	
	4.80 - 5.14	Blk		4.80 - 5.14	Blk									FC2A-514-514-P	
	4.80 - 5.14	Blk		5.15 - 5.57	Wht/Gry									FC2A-514-557-P	
	5.15 - 5.57	Wht/Gry		5.15 - 5.57	Wht/Gry									FC2A-557-557-P	
6"	6.00	Red		6.00	Red	5"	3/8"	5/8"	8"	4	6-1/8"	10-15/16"	24	FC2A-600-600-P	
	6.63	Red		6.63	Red									FC2A-663-663-P	
	6.63	Red		6.90 - 7.20	Blk									FC2A-663-720-P	
	6.63	Red		7.21 - 7.56	Wht/Gry									FC2A-663-756-P	
	6.90 - 7.20	Blk		6.90 - 7.20	Blk									FC2A-720-720-P	
	6.90 - 7.20	Blk		7.21 - 7.56	Wht/Gry									FC2A-720-756-P	
	7.21 - 7.56	Wht/Gry		7.21 - 7.56	Wht/Gry									FC2A-756-756-P	
8"	8.00	Red		8.00	Red	5"	7/16"	5/8"	8"	5	6-1/8"	13-3/16"	34	FC2A-800-800-P	
	8.63	Red		8.63	Red									FC2A-863-863-P	
	8.63	Red		9.05 - 9.40	Blk									FC2A-863-940-P	
	8.63	Red		9.40 - 9.74	Wht/Gry									FC2A-863-974-P	
	9.05 - 9.40	Blk		9.05 - 9.40	Blk									FC2A-940-940-P	
	9.05 - 9.40	Blk		9.40 - 9.74	Wht/Gry									FC2A-940-974-P	
	9.40 - 9.74	Wht/Gry		9.40 - 9.74	Wht/Gry									FC2A-974-974-P	

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve - Ductile iron per ASTM A536 (65-45-12)
- End Rings - Ductile iron per ASTM A536 (65-45-12)
- Bolts and Nuts - Type 304 stainless steel per ASTM A193 and A194
- Coating - Fusion-bonded epoxy. Applied per AWWA C213
- Gasket - NBR (Buna-N) rubber per ASTM D2000
- Certified to ANSI/NSF 61
- Complies with AWWA C219

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

04/29/24

Submitted By: