



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxx-xxx-X-U100 style)



FC2A COUPLING FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S WITH 304 STAINLESS STEEL HARDWARE



NOM. PIPE SIZE (IN.)	GASKET RANGE 1ST HALF CAT. # (IN.)	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. # (IN.)	END RING COLOR	CENTER SLEEVE (IN.)		BOLTS			APPROX. OVERALL LENGTH (IN.)	OAD (IN.)	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
						LENGTH	APPROX. (T) THICKNESS	DIA. (IN.)	LENGTH (IN.)	QTY.					
3	3.13	Red	X	3.13	Red	4	3/8	5/8	6-1/2	3	5-1/8	6-15/16	14	FC2A-313-313-X-U100	
	3.45 - 3.60	Red		3.45 - 3.60	Red									FC2A-360-360-X-U100	
	3.70 - 3.88	Blk		3.70 - 3.88	Blk									FC2A-388-388-X-U100	
	3.91 - 4.06	Blk		3.91 - 4.06	Blk									FC2A-406-406-X-U100	
	4.07 - 4.20	Blk		4.07 - 4.20	Blk									FC2A-420-420-X-U100	
4	4.00	Red	X	4.00	Red	5	3/8	5/8	8	3	6-1/8	8-7/8	16	FC2A-400-400-X-U100	
	4.00	Red		4.50	Red									FC2A-400-450-X-U100	
	4.00	Red		4.80 - 5.14	Blk									FC2A-400-514-X-U100	
	4.50	Red		4.50	Red									FC2A-450-450-X-U100	
	4.50	Red		4.80 - 5.14	Blk									FC2A-450-514-X-U100	
	4.50	Red		5.15 - 5.57	Wht/Gry									FC2A-450-557-X-U100	
	4.80 - 5.14	Blk		4.80 - 5.14	Blk									FC2A-514-514-X-U100	
	4.80 - 5.14	Blk		5.15 - 5.57	Wht/Gry									FC2A-514-557-X-U100	
	5.15 - 5.57	Wht/Gry		5.15 - 5.57	Wht/Gry									FC2A-557-557-X-U100	
6	6.00	Red	X	6.00	Red	5	3/8	5/8	8	4	6-1/8	10-15/16	24	FC2A-600-600-X-U100	
	6.63	Red		6.63	Red									FC2A-663-663-X-U100	
	6.63	Red		6.90 - 7.20	Blk									FC2A-663-720-X-U100	
	6.63	Red		7.21 - 7.56	Wht/Gry									FC2A-663-756-X-U100	
	6.90 - 7.20	Blk		6.90 - 7.20	Blk									FC2A-720-720-X-U100	
	6.90 - 7.20	Blk		7.21 - 7.56	Wht/Gry									FC2A-720-756-X-U100	
	7.21 - 7.56	Wht/Gry		7.21 - 7.56	Wht/Gry									FC2A-756-756-X-U100	
8	8.00	Red	X	8.00	Red	5	7/16	5/8	8	5	6-1/8	13-3/16	34	FC2A-800-800-X-U100	
	8.63	Red		8.63	Red									FC2A-863-863-X-U100	
	8.63	Red		9.05 - 9.40	Blk									FC2A-863-940-X-U100	
	8.63	Red		9.40 - 9.74	Wht/Gry									FC2A-863-974-X-U100	
	9.05 - 9.40	Blk		9.05 - 9.40	Blk									FC2A-940-940-X-U100	
	9.05 - 9.40	Blk		9.40 - 9.74	Wht/Gry									FC2A-940-974-X-U100	
	9.40 - 9.74	Wht/Gry		9.40 - 9.74	Wht/Gry									FC2A-974-974-X-U100	

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve - Ductile iron per ASTM A536
- End Rings - Ductile iron per ASTM A536
- Bolts and Nuts - Type 304 stainless steel per ASTM A193 and A194
- Gasket - Molded SBR rubber per ASTM D2000
- Finish - Shop coat
- Certified to ANSI/NSF 61
- Complies with AWWA C219
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

12/16/25

Submitted By: