



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxxx-xxxx-X style)



10" & 12" STYLE FC2A COUPLINGS (WITH 304 STAINLESS STEEL HARDWARE) FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S



NOM. PIPE SIZE	GASKET RANGE		END RING COLOR	By	GASKET RANGE		END RING COLOR	CENTER SLEEVE		BOLTS		APPROX. OVERALL LGTH.	OAD	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
	1ST HALF CAT. # (IN.)	2ND HALF CAT. # (IN.)			1ST HALF CAT. # (IN.)	2ND HALF CAT. # (IN.)		LGTH.	APPROX. (T) THICKNESS	DIA.	LGTH.	QTY.				
10"	10.75	Red	X	X	10.75	Red	6"	7/16"	5/8"	9"	6	7-1/8"	15-11/16"	48	FC2A-1075-1075-X	
	10.75	Red			11.10 - 11.40	Blk									FC2A-1075-1140-X	
	10.75	Red			11.42 - 11.77	Blk									FC2A-1075-1177-X	
	10.75	Red			11.77 - 12.12	Wht/Gry									FC2A-1075-1212-X	
	11.10 - 11.40	Blk			11.10 - 11.40	Blk									FC2A-1140-1140-X	
	11.10 - 11.40	Blk			11.42 - 11.77	Blk									FC2A-1140-1177-X	
	11.10 - 11.40	Blk			11.77 - 12.12	Wht/Gry									FC2A-1140-1212-X	
	11.42 - 11.77	Blk			11.42 - 11.77	Blk									FC2A-1177-1177-X	
	11.42 - 11.77	Blk			11.77 - 12.12	Wht/Gry									FC2A-1177-1212-X	
	11.77 - 12.12	Wht/Gry			11.77 - 12.12	Wht/Gry									FC2A-1212-1212-X	
12"	12.75	Blk	X	X	12.75	Blk	6"	1/2"	5/8"	9"	7"	7-1/8"	18"	56	FC2A-1275-1275-X	
	12.75	Blk			13.20 - 13.50	Blk									FC2A-1275-1350-X	
	12.75	Blk			13.69 - 14.04	Wht/Gry									FC2A-1275-1404-X	
	12.75	Blk			14.03 - 14.38	Wht/Gry									FC2A-1275-1438-X	
	13.20 - 13.50	Blk			13.20 - 13.50	Blk									FC2A-1350-1350-X	
	13.20 - 13.50	Blk			13.69 - 14.04	Wht/Gry									FC2A-1350-1404-X	
	13.20 - 13.50	Blk			14.03 - 14.38	Wht/Gry									FC2A-1350-1438-X	
	13.69 - 14.04	Wht/Gry			13.69 - 14.04	Wht/Gry									FC2A-1404-1404-X	
	13.69 - 14.04	Wht/Gry			14.03 - 14.38	Wht/Gry									FC2A-1404-1438-X	
	14.03 - 14.38	Wht/Gry			14.03 - 14.38	Wht/Gry									FC2A-1438-1438-X	

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve - Ductile iron per ASTM A536 (65-45-12)
- End Rings - Ductile iron per ASTM A536 (65-45-12)
- Bolts and Nuts - Type 304 stainless steel per ASTM A193 and A194
- Coating - Black alkyd enamel shop coat
- Certified to ANSI/NSF 61
- Gasket - Molded SBR rubber per ASTM D2000
- Complies with AWWA C219

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

03/08/22

Submitted By: