



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxxx-xxxx-Y-U100 style)



**FC2A COUPLING WITH FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S
WITH 304 STAINLESS STEEL HARDWARE AND EPOXY COATING**



NOM. PIPE SIZE (IN.)	GASKET RANGE 1ST HALF CAT. # (IN.)	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. # (IN.)	END RING COLOR	CENTER SLEEVE		BOLTS		APPROX. OVERALL LENGTH (IN.)	OAD (IN.)	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
						LENGTH (IN.)	APPROX. (T) THICKNESS (IN.)	DIA. (IN.)	LENGTH (IN.)					
10	10.75	Red	X	10.75	Red	6	7/16	5/8	9	6	7-1/8	15-11/16	48	FC2A-1075-1075-Y-U100
	10.75	Red		11.10 - 11.40	Blk									FC2A-1075-1140-Y-U100
	10.75	Red		11.42 - 11.77	Blk									FC2A-1075-1177-Y-U100
	10.75	Red		11.77 - 12.12	Wht/Gry									FC2A-1075-1212-Y-U100
	11.10 - 11.40	Blk		11.10 - 11.40	Blk									FC2A-1140-1140-Y-U100
	11.10 - 11.40	Blk		11.42 - 11.77	Blk									FC2A-1140-1177-Y-U100
	11.10 - 11.40	Blk		11.77 - 12.12	Wht/Gry									FC2A-1140-1212-Y-U100
	11.42 - 11.77	Blk		11.42 - 11.77	Blk									FC2A-1177-1177-Y-U100
	11.42 - 11.77	Blk		11.77 - 12.12	Wht/Gry									FC2A-1177-1212-Y-U100
	11.77 - 12.12	Wht/Gry		11.77 - 12.12	Wht/Gry									FC2A-1212-1212-Y-U100
12	12.75	Blk	X	12.75	Blk	6	1/2	5/8	9	7	7-1/8	18	56	FC2A-1275-1275-Y-U100
	12.75	Blk		13.20 - 13.50	Blk									FC2A-1275-1350-Y-U100
	12.75	Blk		13.69 - 14.04	Wht/Gry									FC2A-1275-1404-Y-U100
	12.75	Blk		14.03 - 14.38	Wht/Gry									FC2A-1275-1438-Y-U100
	13.20 - 13.50	Blk		13.20 - 13.50	Blk									FC2A-1350-1350-Y-U100
	13.20 - 13.50	Blk		13.69 - 14.04	Wht/Gry									FC2A-1350-1404-Y-U100
	13.20 - 13.50	Blk		14.03 - 14.38	Wht/Gry									FC2A-1350-1438-Y-U100
	13.69 - 14.04	Wht/Gry		13.69 - 14.04	Wht/Gry									FC2A-1404-1404-Y-U100
	13.69 - 14.04	Wht/Gry		14.03 - 14.38	Wht/Gry									FC2A-1404-1438-Y-U100
	14.03 - 14.38	Wht/Gry		14.03 - 14.38	Wht/Gry									FC2A-1438-1438-Y-U100

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve - Ductile iron per ASTM A536
- End Rings - Ductile iron per ASTM A536
- Bolts and Nuts - Type 304 stainless steel per ASTM A193 and A194
- Finish - Fusion bonded epoxy. Applied per AWWA C213
- Certified to ANSI/NSF 61
- Gasket - SBR rubber per ASTM D2000
- Complies with AWWA C219
- 250 psi working pressure
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

04/23/25

Submitted By: