



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxxx-xxxx style)



10" & 12" STYLE FC2A COUPLINGS FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S



NOM. PIPE SIZE	GASKET RANGE 1ST HALF CAT. #	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. #	END RING COLOR	CENTER SLEEVE		BOLTS		APPROX. OVERALL LGTH.	OAD	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
						LGTH.	APPROX. (T) THICKNESS	DIA.	LGTH.	QTY.				
10"	10.00	Red	X	10.75	Red	6"	7/16"	5/8"	9"	6	7-1/8"	15-11/16"	48	FC2A-1000-1075
	10.75	Red		10.75	Red									FC2A-1075-1075
	10.75	Red		11.10 - 11.40	Blk									FC2A-1075-1140
	10.75	Red		11.42 - 11.77	Blk									FC2A-1075-1177
	10.75	Red		11.77 - 12.12	Wht/Gry									FC2A-1075-1212
	11.10 - 11.40	Blk		11.10 - 11.40	Blk									FC2A-1140-1140
	11.10 - 11.40	Blk		11.42 - 11.77	Blk									FC2A-1140-1177
	11.10 - 11.40	Blk		11.77 - 12.12	Wht/Gry									FC2A-1140-1212
	11.42 - 11.77	Blk		11.42 - 11.77	Blk									FC2A-1177-1177
	11.42 - 11.77	Blk		11.77 - 12.12	Wht/Gry									FC2A-1177-1212
	11.77 - 12.12	Wht/Gry		11.77 - 12.12	Wht/Gry									FC2A-1212-1212
12"	12.75	Blk	X	12.75	Blk	6"	1/2"	5/8"	9"	7	7-1/8"	18"	56	FC2A-1275-1275
	12.75	Blk		13.20 - 13.50	Blk									FC2A-1275-1350
	12.75	Blk		13.69 - 14.04	Wht/Gry									FC2A-1275-1404
	12.75	Blk		14.03 - 14.38	Wht/Gry									FC2A-1275-1438
	13.20 - 13.50	Blk		13.20 - 13.50	Blk									FC2A-1350-1350
	13.20 - 13.50	Blk		13.69 - 14.04	Wht/Gry									FC2A-1350-1404
	13.20 - 13.50	Blk		14.03 - 14.38	Wht/Gry									FC2A-1350-1438
	13.69 - 14.04	Wht/Gry		13.69 - 14.04	Wht/Gry									FC2A-1404-1404
	13.69 - 14.04	Wht/Gry		14.03 - 14.38	Wht/Gry									FC2A-1404-1438
	14.03 - 14.38	Wht/Gry		14.03 - 14.38	Wht/Gry									FC2A-1438-1438

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve: Ductile Iron per ASTM A536 (65-45-12)
- End Rings: Ductile Iron per ASTM A536 (65-45-12)
- Bolts and Nuts: High strength low alloy steel per ASTM A242 or AWWA C111
- Coating: Black Alkyd Enamel Shop Coat NSF 61 Approved
- Gasket: Molded SBR Rubber per ASTM D2000, M4AA810
- NSF61: NSF 61 Approved
- Complies with AWWA C219

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

08/04/2016

Submitted By: