



SUBMITTAL INFORMATION

Steel Coupling - (FC3-xxx-xx-T style)



1/2" THROUGH 8" STEEL COUPLINGS WITH DUCTILE IRON END RINGS



NOM. PIPE SIZE	PIPE O.D. (IN.)	SLEEVE LENGTH	CATALOG NUMBER	NUMBER OF BOLTS	BOLT DIA. & LENGTH	APPROX. WT. LBS.	✓ SUBMITTED ITEM(S)
1/2"	0.84	5"	FC3-084-5-T	2	1/2"x7"	2	
		7"	FC3-084-7-T	2	1/2"x9"	2	
3/4"	1.05	5"	FC3-105-5-T	2	1/2"x7"	2	
		7"	FC3-105-7-T	2	1/2"x9"	3	
1"	1.32	12"	FC3-105-12-T	2	1/2"x14"	3	
		5"	FC3-132-5-T	2	1/2"x7"	3	
		7"	FC3-132-7-T	2	1/2"x9"	3	
1-1/4"	1.66	12"	FC3-132-12-T	2	1/2"x14"	4	
		5"	FC3-166-5-T	2	1/2"x7"	4	
		7"	FC3-166-7-T	2	1/2"x9"	4	
1-1/2"	1.90	12"	FC3-166-12-T	2	1/2"x14"	5	
		5"	FC3-190-5-T	2	1/2"x7"	4	
		7"	FC3-190-7-T	2	1/2"x9"	5	
2"	2.38	12"	FC3-190-12-T	2	1/2"x14"	7	
		5"	FC3-238-5-T	2	5/8"x8"	7	
		5"	FC3-238-5-H-T	3	5/8"x8"	10	
		7"	FC3-238-7-T	2	5/8"x10-1/2"	10	
		7"	FC3-238-7-H-T	3	5/8"x10-1/2"	12	
		12"	FC3-238-12-T	2	5/8"x15"	13	
2-1/2"	2.88	12"	FC3-238-12-H-T	3	5/8"x15"	14	
		5"	FC3-288-5-T	3	5/8"x8"	10	
		7"	FC3-288-7-T	3	5/8"x10-1/2"	11	
		12"	FC3-288-12-T	3	5/8"x15"	14	
		24"	FC3-288-24-T	3	5/8"x27-3/8"	24	
		5"	FC3-350-5-T	4	5/8"x8"	16	
3"	3.50	7"	FC3-350-7-T	4	5/8"x10-1/2"	17	
		12"	FC3-350-12-T	4	5/8"x15"	26	
		24"	FC3-350-24-T	3	5/8"x27-3/8"	35	
		5"	FC3-450-5-T	4	5/8"x8"	16	
4"	4.50	7"	FC3-450-7-T	4	5/8"x10-1/2"	17	
		12"	FC3-450-12-T	4	5/8"x15"	27	
		16"	FC3-450-16-T	4	5/8"x20"	31	
		24"	FC3-450-24-T	4	5/8"x27-3/8"	38	
6"	6.63	5"	FC3-663-5-T	6	5/8"x8"	25	
		7"	FC3-663-7-T	6	5/8"x10-1/2"	31	
		12"	FC3-663-12-T	6	5/8"x15"	50	
		16"	FC3-663-16-T	6	5/8"x20"	65	
		24"	FC3-663-24-T	4	5/8"x27-3/8"	38	
8"	8.63	5"	FC3-863-5-T	6	5/8"x8"	34	
		7"	FC3-863-7-T	6	5/8"x10-1/2"	41	
		12"	FC3-863-12-T	6	5/8"x15"	51	
		16"	FC3-863-16-T	6	5/8"x20"	63	
		24"	FC3-863-24-T	6	5/8"x27-3/8"	78	

"-H" indicates Three Bolt Style

FEATURES

- Center Sleeve: Steel per ASTM A1011 with black Armorguard e-coat (exterior has an additional fusion-bonded epoxy coating)
- End Rings: Ductile iron (Grade 65-45-12) per ASTM A536 with red fusion-bonded epoxy coating
- Gaskets: NBR (Buna-N) per ASTM D2000
Optional armor-tipped gaskets for conductivity are available. Add "-ATG" to end of catalog number.
- Bolts and Nuts: Type 316 stainless steel per ASTM A193 and A194
- Rated Working Pressure: 300 psi

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

08/22/19

Submitted By: