



SUBMITTAL INFORMATION

Fabricated Steel Transition Coupling - (FC5-xxxx-xxxx-A10E style)



STYLE FC5 COUPLINGS FOR JOINING PIPES WITH DIFFERENT O.D.'S



NOM. PIPE SIZE (IN.)	1ST END PIPE O.D. (IN.)	BY	2ND END PIPE O.D. (IN.)	CENTER SLEEVE (T) THICKNESS (IN.)	LENGTH (IN.)	DIA. (IN.)	LENGTH (IN.)	QTY.	APPROX. OVERALL LENGTH (IN.)	OAD (IN.)	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
14	14.00	X	15.30	1/4	10	5/8	13-1/2	9	11-1/8	19-11/16	85	200	FC5-1400-1530-A10E	
	15.30		15.65							20-1/4	91	416	FC5-1530-1565-A10E	
	15.30		15.98							20-5/8	96	416	FC5-1530-1598-A10E	
	15.30		16.22							20-7/8	97	410	FC5-1530-1622-A10E	
16	16.00	X	17.40	1/4	10	5/8	13-1/2	10	11-1/8	22	96	200	FC5-1600-1740-A10E	
	17.40		17.80							22-7/16	102	372	FC5-1740-1780-A10E	
	17.40		17.94							22-9/16	107	372	FC5-1740-1794-A10E	
	17.40		18.16							22-13/16	107	372	FC5-1740-1816-A10E	
18	18.00	X	19.50	1/4	10	5/8	13-1/2	11	11-1/8	24-1/8	107	200	FC5-1800-1950-A10E	
	19.50		19.92							24-9/16	114	337	FC5-1950-1992-A10E	
20	20.00	X	21.60	1/4	10	5/8	13-1/2	12	11-1/8	25-1/4	116	200	FC5-2000-2160-A10E	
	21.60		22.06							26-11/16	124	313	FC5-2160-2206-A10E	
	21.60		22.50							27-1/8	124	313	FC5-2160-2250-A10E	
24	24.00	X	25.80	1/4	10	5/8	13-1/2	14	11-1/8	30-7/16	137	200	FC5-2400-2580-A10E	
	25.80		26.32							30-15/16	146	250	FC5-2580-2632-A10E	
	25.80		26.48							31-1/8	146	250	FC5-2580-2648-A10E	
30	30.00	X	32.00	1/4	10	5/8	13-1/2	16	11-1/8	36-5/8	157	200	FC5-3000-3200-A10E	
	31.74		32.00							36-5/8	165	230	FC5-3174-3200-A10E	
	32.00		32.40							37	166	230	FC5-3200-3240-A10E	
	32.00		32.74							37-3/8	166	230	FC5-3200-3274-A10E	
	36.00		38.30							42-11/16	186	193	FC5-3600-3830-A10E	
36	37.96	X	38.30	1/4	10	5/8	13-1/2	18	11-1/8	42-11/16	225	193	FC5-3796-3830-A10E	
	38.30		38.70							43-13/16	230	193	FC5-3830-3870-A10E	
	38.30		39.16							44-15/16	230	193	FC5-3830-3916-A10E	
	38.30													

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve - Carbon steel per ASTM A36
- End Rings - Cold rolled carbon steel per AISI 1020
- Bolts and Nuts - High strength, low alloy steel per ASTM A536 or AWWA C111
- Finish - Epoxy coated per AWWA C213
- Gasket - SBR rubber per ASTM D2000
- Complies with AWWA C219 standards
- Certified to ANSI/NSF 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

10/31/24

Submitted By: