



SUBMITTAL INFORMATION

Fabricated Steel Transition Coupling - (FC5-xxxx-xxxx-A10R-U style)



STYLE FC5 COUPLINGS FOR JOINING PIPES WITH DIFFERENT O.D.'S



NOM. PIPE SIZE	1ST END PIPE O.D.	BY	2ND END PIPE O.D.	CENTER SLEEVE		BOLTS			APPROX. OVERALL LGTH.	OAD	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
				(T)HICKNESS	LGTH.	DIA.	LGTH.	QTY.						
14"	14.00	X	15.30	1/4"	10"	5/8"	13-1/2"	9	11-1/8"	19-11/16"	85	200	FC5-1400-1530-A10R-U	
	15.30		15.65							20-1/4"	91	416	FC5-1530-1565-A10R-U	
	15.30		15.98							20-5/8"	96	416	FC5-1530-1598-A10R-U	
	15.30		16.22							20-7/8"	97	410	FC5-1530-1622-A10R-U	
16"	16.00	X	17.40	1/4"	10"	5/8"	13-1/2"	10	11-1/8"	22"	96	200	FC5-1600-1740-A10R-U	
	17.40		17.80							22-7/16"	102	372	FC5-1740-1780-A10R-U	
	17.40		17.94							22-9/16"	107	372	FC5-1740-1794-A10R-U	
	17.40		18.16							22-13/16"	107	372	FC5-1740-1816-A10R-U	
18"	18.00	X	19.50	1/4"	10"	5/8"	13-1/2"	11	11-1/8"	24-1/8"	107	200	FC5-1800-1950-A10R-U	
	18.70		19.50							24-1/8"	107	200	FC5-1870-1950-A10R-U	
	19.50		19.92							24-9/16"	114	337	FC5-1950-1992-A10R-U	
	20.00		21.60							25-1/4"	116	200	FC5-2000-2160-A10R-U	
20"	21.60	X	22.06	1/4"	10"	5/8"	13-1/2"	12	11-1/8"	26-11/16"	124	313	FC5-2160-2206-A10R-U	
	21.60		22.50							27-1/8"	124	313	FC5-2160-2250-A10R-U	
	24.00		25.80							30-7/16"	137	200	FC5-2400-2580-A10R-U	
24"	25.80	X	26.32	1/4"	10"	5/8"	13-1/2"	14	11-1/8"	30-15/16"	146	250	FC5-2580-2632-A10R-U	
	25.80		26.48							31-1/8"	146	250	FC5-2580-2648-A10R-U	
	30.00		32.00							36-5/8"	157	200	FC5-3000-3200-A10R-U	
30"	31.74	X	32.00	1/4"	10"	5/8"	13-1/2"	16	11-1/8"	36-5/8"	165	230	FC5-3174-3200-A10R-U	
	32.00		32.40							37"	166	230	FC5-3200-3240-A10R-U	
	32.00		32.74							37-3/8"	166	230	FC5-3200-3274-A10R-U	
	36.00		38.30							42-11/16"	186	193	FC5-3600-3830-A10R-U	
36"	37.96	X	38.30	1/4"	10"	5/8"	13-1/2"	18	11-1/8"	42-11/16"	225	193	FC5-3796-3830-A10R-U	
	38.30		38.70							43-13/16"	230	193	FC5-3830-3870-A10R-U	
	38.30		39.16							44-15/16"	230	193	FC5-3830-3916-A10R-U	

Note: Flexible Couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve: Carbon steel per ASTM A36
- End Rings: Cold rolled carbon steel per AISI 1020
- Bolts and Nuts: High strength low alloy steel per ASTM A242 or AWWA C111
- Coating: Black alkyd enamel shop coat NSF61 approved
- Gasket: Extruded SBR rubber per ASTM D2000 M4AA810 with heat bonded joint
- Complies with AWWA C219 standards

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

04/26/17

Submitted By: