




SUBMITTAL INFORMATION

Adapter Flanges - (FCA-xxx-DxxC style)



FCA COUPLING FOR CONNECTING PLAIN END PIPE TO FLANGED FITTINGS WITH NBR (BUNA-N) GASKET



NOM. PIPE SIZE (IN.)	COUPLING GASKET RANGE (IN.)	FLG. SIZE	END RING BOLTS			DIMENSION (IN.)			SLEEVE LGTH (IN.)		APPROX. OVERALL LENGTH (IN.)	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
			DIA. (IN.)	LGTH. (IN.)	QTY.	A	T / T2	T1	L / L1	L2					
3	3.70 - 3.88	3	5/8	5	3	n/a	3/8	n/a	*7	n/a	8-1/2	21	175	FCA-380-D3C	
4	4.00	4	5/8	5	3	n/a	3/8	n/a	*7	n/a	8-1/2	27	175	FCA-400-D4C	
	4.50 - 4.80					n/a		n/a	*7	n/a	8-1/2	27		FCA-480-D4C	
6	6.00	4	5/8	8	4	1/4	3/8	3/16	5	7	13-1/2	35	175	FCA-600-D4C	
	6.00	6		5		n/a		n/a	*7	n/a	8-1/2	37		FCA-600-D6C	
	6.30	4		8		1/4		3/16	5	7	13-1/2	40		FCA-630-D4C	
	6.30	6		5		n/a		n/a	*7	n/a	8-1/2	38		FCA-630-D6C	
	6.63 - 6.90	4		8		1/4		3/16	5	7	13-1/2	41		FCA-690-D4C	
	6.63 - 6.90	6		5		n/a		n/a	*7	n/a	8-1/2	36		FCA-690-D6C	
8	8.00	6	5/8	8	5	1/4	1/4	3/16	5	7	13-1/2	45	175	FCA-800-D6C	
	8.00	8		5		n/a		n/a	10	n/a	11-1/2	49		FCA-800-D8C	
	8.63 - 9.05	4		8		1/4		3/16	5	7	13-1/2	46		FCA-905-D4C	
	8.63 - 9.05	6		8		1/4		3/16	5	7	13-1/2	50		FCA-905-D6C	
	8.63 - 9.05	8		5		n/a		n/a	10	n/a	11-1/2	47		FCA-905-D8C	
	9.05 - 9.40	8		5		n/a		n/a	10	n/a	11-1/2	50		FCA-940-D8C	
10	10.00	10	5/8	5	6	n/a	1/4	n/a	10	n/a	11-1/2	65	175	FCA-1000-D10C	
	10.75	10		5		n/a		n/a	10	n/a	11-1/2	61		FCA-1075-D10C	
	11.10 - 11.46	8		8		1/4		3/16	5	7	13-1/2	71		FCA-1146-D8C	
	11.10 - 11.46	10		5		n/a		n/a	10	n/a	11-1/2	59		FCA-1146-D10C	
12	12.00	12	5/8	5	6	n/a	1/4	n/a	10	n/a	11-1/2	79	175	FCA-1200-D12C	
	12.75	12		5		n/a		n/a	10	n/a	11-1/2	87		FCA-1275-D12C	
	13.20 - 13.56	10		8		1/4		1/4	5	7	13-1/2	90		FCA-1356-D10C	
	13.20 - 13.56	12		5		n/a		n/a	10	n/a	11-1/2	81		FCA-1356-D12C	

Note: Flexible couplings do not restrain axial forces on piping.

*1/4" thick sleeve reducer used to attach sleeve to flange

FEATURES

- Sleeve - Carbon steel per ASTM A36
- Center Ring - Carbon steel per ASTM A36
- End Rings - Ductile iron per ASTM A536
- Flange - Class D AWWA C207
- Bolts and Nuts - High strength, low alloy steel per ASTM A242 or AWWA C111
- Gasket - NBR (Buna-N) rubber per ASTM D2000
- Finish - Epoxy coated
- Certified to ANSI/NSF 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

08/01/24

Submitted By: