



SUBMITTAL INFORMATION

Adapter Flanges - (FCA-xxx-FxxM style)



3" - 12" STYLE FCA COUPLINGS FOR CONNECTING PLAIN END PIPE TO FLANGED FITTINGS



NOM. PIPE SIZE	COUPLING GASKET RANGE (IN.)	FLG. SIZE	END RING BOLTS DIA.	LGTH.	QTY.	A	T / T2	T1	L / L1	L2	APPROX. OVERALL LENGTH	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
3"	3.70 - 3.88	3"	5/8"	5"	3	n/a	3/8"	n/a	*7"	n/a	8-1/2"	21	175	FCA-380-F3M	
4"	4.00	4"	5/8"	5"	3	n/a	3/8"	n/a	*7"	n/a	8-1/2"	27	175	FCA-400-F4M	
	4.50 - 4.80					n/a		n/a	*7"	n/a	8-1/2"	27		FCA-480-F4M	
6"	6.00	4"	5/8"	8"	4	1/4"	3/8"	3/16"	5"	7"	13-1/2"	40	175	FCA-600-F4M	
	6.00	6"		5"		n/a		n/a	*7"	n/a	8-1/2"	37		FCA-600-F6M	
	6.30	4"		8"		1/4"		3/16"	5"	7"	13-1/2"	40		FCA-630-F4M	
	6.30	6"		5"		n/a		n/a	*7"	n/a	8-1/2"	38		FCA-630-F6M	
	6.63 - 6.90	4"		8"		1/4"		3/16"	5"	7"	13-1/2"	41		FCA-690-F4M	
	6.63 - 6.90	6"		5"		n/a		n/a	*7"	n/a	8-1/2"	36		FCA-690-F6M	
8"	8.00	6"	5/8"	8"	5	1/4"	1/4"	3/16"	5"	7"	13-1/2"	48	175	FCA-800-F6M	
	8.00	8"		5"		n/a		n/a	10"	n/a	11-1/2"	49		FCA-800-F8M	
	8.63 - 9.05	4"		8"		1/4"		3/16"	5"	7"	13-1/2"	46		FCA-905-F4M	
	8.63 - 9.05	6"		8"		1/4"		3/16"	5"	7"	13-1/2"	50		FCA-905-F6M	
	8.63 - 9.05	8"		5"		n/a		n/a	10"	n/a	11-1/2"	47		FCA-905-F8M	
10"	10.00	10"	5/8"	5"	6	n/a	1/4"	n/a	10"	n/a	11-1/2"	65	175	FCA-1000-F10M	
	10.75	10"		5"		n/a		n/a	10"	n/a	11-1/2"	61		FCA-1075-F10M	
	11.10 - 11.46	8"		8"		1/4"		3/16"	5"	7"	13-1/2"	70		FCA-1146-F8M	
	11.10 - 11.46	10"		5"		n/a		n/a	10"	n/a	11-1/2"	59		FCA-1146-F10M	
12"	12.00	12"	5/8"	5"	6	n/a	1/4"	n/a	10"	n/a	11-1/2"	79	175	FCA-1200-F12M	
	12.75	12"		5"		n/a		n/a	10"	n/a	11-1/2"	87		FCA-1275-F12M	
	13.20 - 13.56	10"		8"	7	1/4"		1/4"	5"	7"	13-1/2"	90		FCA-1356-F10M	
	13.20 - 13.56	12"		5"		n/a		n/a	10"	n/a	11-1/2"	81		FCA-1356-F12M	

Note: Flexible couplings do not restrain axial forces on piping.

*1/4" thick sleeve reducer used to attach sleeve to flange

FEATURES

- Sleeve - Carbon steel per ASTM A36
- Center Ring - Carbon steel per ASTM A36
- End Ring - Ductile iron per ASTM A536
- Flange - Class F AWWA C207
- Bolts and Nuts - Type 304 stainless steel per ASTM A193 and A194
- Gasket - EPDM rubber per ASTM D2000
- Finish - Black alkyd enamel shop coat - NSF 61 approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

09/15/20

Submitted By: