



SUBMITTAL INFORMATION

Adapter Flanges - (FCA-xxxx-DxxT-U100 style)



**3"-12" STYLE FCA COUPLINGS (WITH EPOXY COATING AND 316 STAINLESS STEEL HARDWARE)
FOR CONNECTING PLAIN END PIPE TO FLANGED FITTINGS**



NOM. PIPE SIZE	COUPLING GASKET RANGE (IN.)	FLG. SIZE	END RING BOLTS			DIMENSION			SLEEVE LGTH	APPROX. OVERALL LENGTH	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)	
			DIA.	LGTH.	QTY.	A	T / T2	T1							
3"	3.70 - 3.88	3"	5/8"	5"	3	n/a	3/8"	n/a	7"	n/a	8-1/2"	21	175	FCA-380-D3T-U100	
	3.80 - 3.96								n/a	7"	n/a	8-1/2"	21	175	FCA-396-D3T-U100
4"	4.00	4"	5/8"	5"	3	n/a	3/8"	n/a	7"	n/a	8-1/2"	27	175	FCA-400-D4T-U100	
	4.50 - 4.80								n/a	7"	n/a	8-1/2"	27	FCA-480-D4T-U100	
6"	6.00	4"	5/8"	8"	4	1/4"	3/8"	1/4"	3/16"	5"	7"	13-1/2"	40	175	FCA-600-D4T-U100
	6.00								n/a	7"	n/a	8-1/2"	37		FCA-600-D6T-U100
	6.30								3/16"	5"	7"	13-1/2"	40		FCA-630-D4T-U100
	6.30								n/a	7"	n/a	8-1/2"	38		FCA-630-D6T-U100
	6.63 - 6.90								3/16"	5"	7"	13-1/2"	41		FCA-690-D4T-U100
	6.63 - 6.90								n/a	7"	n/a	8-1/2"	36		FCA-690-D6T-U100
8"	8.00	6"	5/8"	8"	5	1/4"	1/4"	1/4"	3/16"	5"	7"	13-1/2"	48	175	FCA-800-D6T-U100
	8.00								n/a	10"	n/a	11-1/2"	49		FCA-800-D8T-U100
	8.63 - 9.05								3/16"	5"	7"	13-1/2"	46		FCA-905-D4T-U100
	8.63 - 9.05								3/16"	5"	7"	13-1/2"	50		FCA-905-D6T-U100
	8.63 - 9.05								n/a	10"	n/a	11-1/2"	47		FCA-905-D8T-U100
10"	10.00	10"	5/8"	5"	6	n/a	1/4"	1/4"	n/a	10"	n/a	11-1/2"	65	175	FCA-1000-D10T-U100
	10.75								n/a	10"	n/a	11-1/2"	61		FCA-1075-D10T-U100
	11.10 - 11.46								3/16"	5"	7"	13-1/2"	70		FCA-1146-D8T-U100
	11.10 - 11.46								n/a	10"	n/a	11-1/2"	59		FCA-1146-D10T-U100
12"	12.00	12"	5/8"	5"	7	n/a	1/4"	1/4"	n/a	10"	n/a	11-1/2"	79	175	FCA-1200-D12T-U100
	12.75								n/a	10"	n/a	11-1/2"	87		FCA-1275-D12T-U100
	13.20 - 13.56								1/4"	5"	7"	13-1/2"	90		FCA-1356-D10T-U100
	13.20 - 13.56								n/a	10"	n/a	11-1/2"	81		FCA-1356-D12T-U100

Note: Flexible couplings do not restrain axial forces on piping.

*1/4" thick sleeve reducer used to attach sleeve to flange

FEATURES

- Sleeve - Carbon steel per ASTM A36
- Center Ring - Carbon steel per ASTM A36
- End Rings - Ductile iron per ASTM A536
- Flange - Class D AWWA C207
- Bolts and Nuts - Type 316 stainless steel per ASTM A193 and A194
- Gasket - NBR (Buna-N) rubber per ASTM D2000
- Finish - Fusion-bonded epoxy - NSF 61 approved
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.

 <p>The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 www.fordmeterbox.com</p>	<p>Submitted By:</p>
	12/20/22