



SUBMITTAL INFORMATION

Adapter Flanges - (FCA-xxxx-DxxX-U style)



14" - 24" STYLE FCA COUPLINGS FOR CONNECTING PLAIN END PIPE TO FLANGED FITTINGS



NOM. PIPE SIZE	COUPLING GASKET RANGE	FLG SIZE	END RING BOLTS			DIMENSION		SLEEVE LGTH		APPROX. OVERALL LENGTH	APPROX. WT. LBS.	RATED WORKING PRESSURE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
			DIA.	LGTH.	QTY.	A	T	L1	L2					
14"	13.69 - 14.04	12"	5/8"	8"	7	3/8"	1/4"	5"	7"	13-7/8"	107	175	FCA-1404-D12X-U	
	15.30 - 15.70	10"		8"	9	3/8"		5"	7"	13-7/8"	133	175	FCA-1570-D10X-U	
	15.30 - 15.70	12"		8"		3/8"		5"	7"	13-7/8"	-	175	FCA-1570-D12X-U	
	15.30	14"		5"		n/a		10"	n/a	11-1/2"	108	150	FCA-1530-D14X-U	
	15.70	14"		5"		n/a		10"	n/a	11-1/2"	114	150	FCA-1570-D14X-U	
16"	16.00 - 16.35	14"	5/8"	8"	10	1/2"	1/4"	5"	7"	14-1/8"	166	150	FCA-1635-D14X-U	
	16.00	16"		5"		n/a		10"	n/a	11-1/2"	128	150	FCA-1600-D16X-U	
	17.40 - 17.80	12"		8"		1/2"		5"	7"	14-1/8"	152	175	FCA-1780-D12X-U	
	17.40	16"		5"		n/a		10"	n/a	11-1/2"	134	150	FCA-1740-D16X-U	
	17.80	16"		5"		n/a		10"	n/a	11-1/2"	135	150	FCA-1780-D16X-U	
18"	18.00	18"	5/8"	5"	11	n/a"	1/4"	10"	n/a	11-5/8"	136	150	FCA-1800-D18X-U	
	19.50 - 20.00	14"		8"		5/8"		5"	7"	14-1/4"	153		FCA-2000-D14X-U	
	19.50 - 20.00	16"		8"		5/8"		5"	7"	14-1/4"	-		FCA-2000-D16X-U	
	19.50	18"		5"		n/a		10"	n/a	11-5/8"	140		FCA-1950-D18X-U	
	19.50 - 20.00	18"		8"		5/8"		5"	7"	14-3/8"	192		FCA-2000-D18X-U	
20"	20.00	20"	5/8"	5"	12	n/a	1/4"	10"	n/a	11-3/4"	160	150	FCA-2000-D20X-U	
	21.60 - 22.06	16"		8"		5/8"		5"	7"	14-3/8"	200		FCA-2206-D16X-U	
	21.60 - 22.06	18"		8"		5/8"		5"	7"	14-3/8"	-		FCA-2206-D18X-U	
	21.60	20"		5"		n/a		10"	n/a	11-3/4"	164		FCA-2160-D20X-U	
	22.06	20"		5"		n/a		10"	n/a	11-3/4"	169		FCA-2206-D20X-U	
24"	24.00	20"	5/8"	*5"	14	7/8"	1/4"	5"	7"	14-3/4"	-	150	FCA-2400-D20X-U	
	24.00	24"		5"		n/a		10"	n/a	11-7/8"	204		FCA-2400-D24X-U	
	25.80	20"		*5"		7/8"		5"	7"	14-3/4"	-		FCA-2580-D20X-U	
	25.80	24"		5"		n/a		10"	n/a	11-7/8"	209		FCA-2580-D24X-U	

Note: Flexible couplings do not restrain axial forces on piping.

* 24" reducing coupling sleeves employ weld-on bolt loops rather than connecting to center ring.

FEATURES

- Sleeve: Carbon steel per ASTM A36
- Center Ring: Carbon steel per ASTM A36
- End Ring: Ductile iron per ASTM A536 or carbon steel per ASTM A36
- Bolts and Nuts: 18-8 type 304 stainless steel per ASTM A193 and A194
- Flange: Class D AWWA C207
- Gasket: SBR rubber per ASTM D2000
- Finish: Black shop coat

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

01/09/17

Submitted By: