



SUBMITTAL INFORMATION


Dismantling Joint - (FDJ-DxxA-U style)



DISMANTLING JOINT - CLASS D FLANGE



Style A



Style B

NOMINAL SIZE	CATALOG NUMBER	STYLE	NOMINAL LENGTH	MINIMUM LENGTH	MAXIMUM LENGTH	APPROX. WEIGHT LBS.	✓ SUBMITTED ITEM(S)
3"	FDJ-D3A-U	B	12-1/8"	10-1/2"	13-3/4"	31	
4"	FDJ-D4A-U	A	8-1/16"	7-1/8"	9"	39	
6"	FDJ-D6A-U	B	12-3/4"	11-1/4"	14-1/4"	67	
8"	FDJ-D8A-U	B	15"	13-1/4"	16-3/4"	88	
10"	FDJ-D10A-U	B	15-1/4"	13-1/2"	17"	93	
12"	FDJ-D12A-U	B	15-1/2"	14"	17"	165	
14"	FDJ-D14A-U	B	14-3/4"	13-1/4"	16-1/4"	192	
16"	FDJ-D16A-U	B	15"	13-1/2"	16-1/2"	249	
18"	FDJ-D18A-U	B	15-1/8"	13-5/8"	16-5/8"	270	
20"	FDJ-D20A-U	B	15-1/8"	13-5/8"	16-5/8"	310	
24"	FDJ-D24A-U	B	15-1/4"	13-3/4"	16-3/4"	396	
30"	FDJ-D30A-U	B	15-7/8"	14-3/4"	17"	605	
36"	FDJ-D36A-U	B	16-1/4"	15-1/4"	17-1/4"	971	
42"	FDJ-D42A-U	B	15-1/2"	13-3/4"	17-1/4"	1275	
48"	FDJ-D48A-U	B	17-3/8"	15-3/4"	19"	1567	

FEATURES

- Flange: AWWA Class D flange, drilling per ANSI/AWWA C110/A21, ANSI B16.5 150 lb.
- Flange and adjusting pipe: ASTM A36 carbon steel
- Gaskets - Extruded EPDM rubber per ASTM D2000
- Bolts and Nuts - High strength, low alloy steel per AWWA C111
- Fusion bonded epoxy coating - NSF 61 Approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

06/23/21

Submitted By: