


SUBMITTAL INFORMATION





RESTRAINED DISMANTLING JOINT - CLASS E FLANGE



Nominal	CATALOG	Nominal	Мінімим	Махімим	RESTRA	INT RODS	APPROX.	✓ SUBMITTED
SIZE	Number	LENGTH	LENGTH	LENGTH	Number	Size	WEIGHT	ITEM(S)
4"	FDJ-E4R-R	13-1/8"	11-1/2"	14-3/4"	2	5/8" X 24"	70	
6"	FDJ-E6R-R	14"	12-1/2"	15-1/2"	2	3/4" X 24"	92	
8"	FDJ-E8R-R	16-5/8"	14-7/8"	18-3/8"	4	3/4" X 26"	126	
10"	FDJ-E10R-R	17"	15-1/4"	18-3/4"	3	7/8" X 26"	156	
12"	FDJ-E12R-R	17-3/8"	15-7/8"	18-7/8"	2	7/8" X 26"	186	
14"	FDJ-E14R-R	16-5/8"	15-1/8"	18-1/8"	2	1" X 26"	358	
16"	FDJ-E16R-R	17"	15-1/2"	18-1/2"	4	1" X 30"	375	
18"	FDJ-E18R-R	17-1/4"	15-3/4"	18-3/4"	4	1-1/8" X 30"	390	
20"	FDJ-E20R-R	17-5/8"	16-1/8"	19-1/8"	4	1-1/8" X 30"	608	
24"	FDJ-E24R-R	18"	16-1/2"	19-1/2"	4	1-1/4" X 30"	660	
30"	FDJ-E30R-R	18-7/8"	17-3/4"	20"	6	1-1/4" X 36"	1,345	
36"	FDJ-E36R-R	19-1/4"	18-1/4"	20-1/4"	6	1-1/2" x 36"	-	
42"	FDJ-E42R-R	18-3/4"	17"	20-1/2"	8	1-1/2" x 36"	-	
48"	FDJ-E48R-R	20-5/8"	19"	22-1/4"	10	1-1/2" x 36"	-	

FEATURES

- Flange AWWA Class E flange, drilling per ANSI/AWWA C110/A21, ANSI B16.5 150 lb
- Flange and adjusting pipe A36 carbon steel
- Gaskets Extruded SBR rubber per ASTM D2000
- Bolts and Nuts High strength, low alloy steel per AWWA C111
- Tie rods Grade B7 steel per ASTM A193
- Coating Black shop coat NSF 61 approved
- Rated for 275 psi working pressure

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

|--|