


SUBMITTAL INFORMATION

Repair Clamps - (FS1-xxx-Length-V style)



2" TO 4" ALL 316 STAINLESS STEEL CIRCLE REPAIR CLAMPS

Optional Stainless Taps

Type 316 stainless steel TIG welded to band. Available with AWWA or I.P. threads.

Band

Type 316 stainless steel

Lifter Bar

Type 316 heavy gauge stainless steel

Sidebar

Type 316 heavy gauge stainless steel

Lug


Type 316 heavy gauge stainless steel

Armor

Heavy gauge stainless steel, mold bonded into the gasket to ensure uniform compression against the pipe

Gasket

Gridded virgin EPDM compounded for water service, per ASTM D2000. NBR (Buna-N) is optional.



Bolts & Nuts

Type 316 stainless steel nuts and washers. Nuts are coated to prevent galling.

OUTLET THREAD TAP CODE

CC (AWWA) Thread			IP Thread		
THREAD	CODE NUMBER	MIN. CLAMP SZ.	THREAD	CODE NUMBER	MIN. CLAMP SZ.
3/4" CC	-CC3	2.63"	3/4" IP	-IP3	2.63"
1" CC	-CC4	2.63"	1" IP	-IP4	2.63"
1-1/4" CC	-CC5	3.25"	1-1/4" IP	-IP5	3.25"
1-1/2" CC	-CC6	3.25"	1-1/2" IP	-IP6	3.25"
2" CC	-CC7	4.00"	2" IP	-IP7	3.70"

NOM. PIPE SIZE (IN.)	PIPE O.D. RANGE (IN.)	LENGTH AND APPROXIMATE WEIGHT (LBS.)									BOLT SIZE	BAND THICKNESS	CATALOG NUMBER FS1-xxx-LENGTH-V	✓ SUBMITTED ITEM(S)
		4"	6"	7.5"	10"	12.5"	15"	20"	24"	30"				
2	2.05 - 2.25	3	4	4	5	5	8	n/a	n/a	n/a	1/2" 13 UNC	24 GA.	FS1-225-xx-Length-V	
	2.35 - 2.63	N/A	4	4	5	5	8	10	13	17			FS1-263-xx-Length-V	
2-1/4 - 2-1/2	2.70 - 3.00	N/A	4	5	5	6	8	11	13	17			FS1-300-xx-Length-V	
	2.97 - 3.25												FS1-325-xx-Length-V	
3	3.42 - 3.66	N/A	4	5	5	6	9	12	14	17			FS1-366-xx-Length-V	
	3.46 - 3.70												FS1-370-xx-Length-V	
	3.73 - 4.00												FS1-400-xx-Length-V	
	3.96 - 4.25												FS1-425-xx-Length-V	
4	4.06 - 4.35	N/A	5	5	6	7	9	14	15	18			FS1-435-xx-Length-V	
	4.37 - 4.65												FS1-465-xx-Length-V	
	4.45 - 4.73												FS1-473-xx-Length-V	
	4.74 - 5.14	N/A	5	6	7	8	10	14	16	21	FS1-514-xx-Length-V			
	4.95 - 5.35										FS1-535-xx-Length-V			
	5.22 - 5.62										FS1-562-xx-Length-V			
Number of Bolts		1	2	2	3	3	4	6	7	9				

FEATURES

- NBR (Buna-N) gasket and conductivity strips are available
- Also available in two-and three-section clamps for a wider range of pipe sizes and tolerances
- Optional outlet taps are available for repair of service line pull-outs. Add tapping code to catalog number
- All welds are fully passivated to restore corrosion resistant characteristics of stainless steel
- Certified to ANSI/NSF Standard 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

03/04/25

Submitted By: