

SUBMITTAL INFORMATION

Repair Clamps - (FSP2-xxxx style)



4" TO 16" TWO SECTION ALL STAINLESS STEEL CIRCLE REPAIR CLAMPS FOR HDPE PIPE



Washers:
Belleville Spring Washer 17-7
PH stainless steel.

Note: Quantity may vary.

Lifter Bar

18-8 type 304 heavy gauge stainless steel

Sidebar

18-8 type 304 heavy gauge stainless steel


Lug

18-8 type 304 heavy gauge stainless steel

<u>Armor</u>

18-8 type 304 heavy gauge stainless steel, molded into the gasket to ensure uniform compression against the pipe Bolts & Nuts

18-8 type 304 stainless steel nuts and washers. Nuts are coated to prevent galling.



Optional Stainless Taps


18-8 type 304 stainless steel tap tig welded to band. Available with AWWA, or I.P. threads.



SBR per ASTM D2000 4AA610, Optional Buna-N, Nitrile

OUILLI TIMLAD TAI OUDL							
CC (AWV	NA) Thread	IP Thread					
THREAD	CODE NUMBER	THREAD	CODE NUMBER				
3/4" CC	-CC3	3/4" IP	-IP3				
1" CC	-CC4	1" IP	-IP4				
1-1/4" CC	-CC5	1-1/4" IP	-IP5				
1-1/2" CC	-CC6	1-1/2" IP	-IP6				
2" CC	-CC7	2" IP	-IP7				

OUTLET THREAD TAP CODE



Nom. PIPE	PIPE O.D.	CATALOG	LENGTH AND APPROXIMATE SHIPPING WEIGHT LBS.							
SIZE	RANGE	Number	7.5"	10"	12.5"	15"	20"	24"	30"	36"
4"	4.50	FSP2-450xLength	11 Lbs.	14 Lbs.	18 Lbs.	26 Lbs.	32 Lbs.	38 Lbs.	N/A	N/A
4	4.80	FSP2-480xLength								IN/A
6"	6.63	FSP2-663xLength	12	15	19	28	35	42	45 lbs	59 lbs
б	6.90	FSP2-690xLength								
8"	8.63	FSP2-863xLength	13	17	21	30	38	46	51	63
0	9.05	FSP2-905xLength								
10"	10.75	FSP2-1075xLength	N/A	18	23	32	41	50	54	65
10	11.10	FSP2-1110xLength								
12"	12.75	FSP2-1275xLength	N/A	19 25	25	34	44	54	57	68
12	13.20	FSP2-1320xLength			34	44	54	5/	00	
14"	14.00	FSP2-1400xLength	N/A	20	27	36	47	58	63	75
14	15.30	FSP2-1530xLength								
16"	16.00	FSP2-1600xLength	N/A	22	29	38	50	62	66	78
10	17.40	FSP2-1740xLength								
	Number of Studs 4 6 6-8* 8 12 14 18		18	20						

^{* 12.5&}quot; long clamps in the 10" thru 16" nominal pipe size have 8 studs.

FEATURES

- All welds are fully passivated to restore corrosion resistant characteristics of stainless steel
- Manufactured in the U.S.A.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

43		
/06/16		