


SUBMITTAL INFORMATION

Steel Tapping Sleeve - (FTS-xxxx-x-U style)




STEEL TAPPING SLEEVE

Flange - ASTM A36 carbon steel with recess per MSS SP-60 to accept standard tapping valves. Flange conforms to AWWA C207 Class D ANSI 150# drilling.

3/4-14 Steel Test Plug

Bolts and Nuts - High strength, low alloy steel heavy hex nuts are coated to prevent galling.

Finish - Shop coat



NOM PIPE SIZE	SLEEVE OD RANGE (IN.)	FLANGE SIZE CODE	NOMINAL DIMENSIONS - INCHES				MIN. NO. OF BOLTS	SIZE OF BOLTS (IN.)	APPROX. WT. LBS.	SLEEVE NUMBER*	✓ SUBMITTED ITEM(S)
			COUNTER- BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH					
			A	B	C	D					
24"	25.71-26.41 26.55-27.25 27.26-27.96 28.14-28.84	2	3-3/64	2-1/16	5-3/16	12	6	3/4	142	FTS-2641-x-U FTS-2725-x-U FTS-2796-x-U FTS-2884-x-U	
		3	4-3/64	3-1/16	5-3/16	12	6	3/4	144		
		4	5-3/64	4-1/8	5-3/16	12	6	3/4	144		
		6	7-3/64	6-1/4	5-3/16	12	6	3/4	152		
		8	9-3/64	8-1/4	5-3/16	16	8	3/4	220		
		10	11-3/64	10-1/4	5-3/16	20	10	3/4	262		
		12	13-3/64	12-1/4	5-3/16	24	12	3/4	330		
		14	15-5/16	13-1/2	6-1/4	28	14	3/4	420		
		16	17-5/16	15-1/2	6-1/4	32	16	3/4	495		
		18	19-17/32	17-1/2	6-1/4	36	18	3/4	550		
30"	29.78-30.48 30.48-31.18 31.52-32.22	2	3-3/64	2-1/16	5-3/16	12	6	3/4	160	FTS-3048-x-U FTS-3118-x-U FTS-3222-x-U	
		3	4-3/64	3-1/16	5-3/16	12	6	3/4	162		
		4	5-3/64	4-1/8	5-3/16	12	6	3/4	162		
		6	7-3/64	6-1/4	5-3/16	12	6	3/4	168		
		8	9-3/64	8-1/4	5-3/16	16	8	3/4	222		
		10	11-3/64	10-1/4	5-3/16	20	10	3/4	283		
		12	13-3/64	12-1/4	5-3/16	24	12	3/4	350		
		14	15-5/16	13-1/2	6-1/4	28	14	3/4	520		
		16	17-5/16	15-1/2	6-1/4	32	16	3/4	550		
		18	19-17/32	17-1/2	6-1/4	36	18	3/4	580		
		20	21-17/32	19-1/2	6-1/4	40	20	3/4	682		
		24	25-17/32	23-1/2	6-1/4	48	24	3/4	832		
		30	31-1/16	29-9/16	6-1/4	60	30	3/4	981		

***To Order:** Add flange size to the sleeve number. Example: A 16" flange on 24" cast iron pipe would be FTS-2641-16-U. For stainless steel nuts and bolts option, add "-SH" to the catalog number. Example: FTS-2641-16-SH-U.

Note: A 1" undersize cutter is required for flanges 14" and larger. Oversize outlets are available by special request.

FEATURES

- Heavy welded steel meeting ASTM A36 36,000 psi minimum yield
- Bolts and nuts are made of high strength, low alloy steel per AWWA C111
- Ring style gasket is NBR (Buna-N) per ASTM D2000
- Certified to NSF/ANSI 61
- Rated for 250 psi up to 24" outlets. 30"-36" outlets rated for 200 psi. Ratings not to exceed the rating of the pipe.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

09/10/25

Submitted By: