


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve 4"-12" - (FTSAS-xxx-x-U100 style)



STAINLESS STEEL TAPPING SLEEVE WITH STAINLESS STEEL OR CARBON STEEL FLANGE

Flange - Type 304 stainless steel with recess per MSS SP60 to accept standard tapping valves. Flange conforms to AWWA C228 Class SD ANSI 150# drilling. Optional carbon steel flange, per AWWA C207, is available.

Bolts, Nuts, & Washers - Type 304 stainless steel per ASTM A193 and A194. Heavy hex nuts and washers are coated to prevent galling and maximize bolt efficiency.

Outlet Pipe - Type 304 stainless steel

3/4-14 No-Lead Brass Test Plug

Outlet Gasket - Virgin NBR (Buna-N) compounded for water service, per ASTM D2000. Outlet gasket ensures seal of outlet area. Partial Pad Gasket - SBR component for water service, per ASTM D2000.

3/16" lug (1/4" lug if using a 3/4" bolt.)

NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	SLEEVE NUMBER	FLANGE SIZE CODE	NOMINAL DIMENSIONS - INCHES				MIN. NO. OF BOLTS	SIZE OF BOLTS	APPROX. WEIGHT LBS.	✓ SUBMITTED ITEM(S)
				COUNTER-BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH				
				A	B	C	D				
4"	4.50-4.80	FTSAS-480-x-U100	2	3-1/16	3-1/4	5-3/8	15	8	5/8	39	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8	40	
			4	5-1/16	4-1/4	4-15/16	15	8	5/8	40	
6"	6.63-7.00 6.90-7.30	FTSAS-700-x-U100 FTSAS-730-x-U100	2	3-1/16	3-1/4	5-3/8	15	8	5/8	65	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8	66	
			4	5-1/16	4-1/4	4-15/16	15	8	5/8	67	
8"	8.63-9.05 9.05-9.30	FTSAS-905-x-U100 FTSAS-930-x-U100	6	7-1/16	6-13/32	5-1/4	15	8	5/8	74	
			2	3-1/16	3-1/4	5-3/8	15	8	5/8	83	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8	84	
10"	10.75-11.10 11.10-11.40 11.40-11.70	FTSAS-1110-x-U100 FTSAS-1140-x-U100 FTSAS-1170-x-U100	4	5-1/16	4-1/4	4-15/16	15	8	5/8	85	
			6	7-1/16	6-13/32	5-1/4	15	8	5/8	89	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8	94	
12"	12.75-13.20 13.20-13.50	FTSAS-1320-x-U100 FTSAS-1350-x-U100	2	3-1/16	3-1/4	5-3/8	15	8	5/8	88	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8	89	
			4	5-1/16	4-1/4	4-15/16	15	8	5/8	90	
			6	7-1/16	6-13/32	5-1/4	15	8	5/8	93	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8	99	
			10	11-1/16	10-15/32	5-7/8	20	12	3/4	111	
			2	3-1/16	3-1/4	5-3/8	15	8	5/8	96	
			3	4-1/16	3-1/4	4-15/16	15	8	5/8	97	
			4	5-1/16	4-1/4	4-15/16	15	8	5/8	98	
			6	7-1/16	6-13/32	5-1/4	15	8	5/8	102	
			8	9-1/16	8-13/32	5-3/8	20	12	5/8	108	
			10	11-1/16	10-15/32	5-7/8	20	12	3/4	188	
			12	13-1/16	12-13/32	6	24	14	3/4	207	

* To order: Add flanged outlet size to catalog number. Example: The complete FTSAS catalog number for a 6" pipe (6.90 O.D.) with a 4" stainless steel flange is FTSAS-730-4-U100. For a carbon steel flange, add "A" to the catalog number. Example: FTSAS-730-4A-U100

FEATURES

- Body, straps and UNC threaded bolts are made of type 304 stainless steel. Flange can be either stainless steel or ASTM A36 carbon steel. All sleeves are fully passivated for corrosion resistance.
- Outlet gasket is NBR (Buna-N) per ASTM 2000.
- Rated for up to 250 psi. Rating not to exceed the pressure rating of the pipe.
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

04/03/24

Submitted By: