


SUBMITTAL INFORMATION

Steel Tapping Sleeve - (FTSC-xxxx-x-AH style)





STEEL TAPPING SLEEVE - 24" TO 30"

Flange - ASTM A36 Carbon Steel - Flat face, recessed per MSS SP-60 for standard tapping valve. Flange conforms to AWWA C207

3/4-14 No-Lead Brass
Test Plug

Bolts and Nuts -
High strength, low alloy

Finish - Fusion-bonded epoxy



Gasket - NBR (Buna-N)
per ASTM D2000

Body - Heavy welded steel with a
recessed groove or retaining rings to
retain the gasket.

NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	BY	FLANGE SIZE CODE*	NOMINAL DIMENSIONS - INCHES				MIN. NO. OF BOLTS	BOLT DIA.	APPROX. WT. LBS.	SLEEVE NUMBER*	✓ SUBMITTED ITEM(S)
				COUNTER- BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH					
24"	25.71-26.41 26.55-27.25 27.26-27.96 28.14-28.84			2	3-3/64	2-1/16	5-3/16	12	6	3/4	142	FTSC-2641-x-AH
				3	4-3/64	3-1/16	5-3/16	12	6	3/4	144	FTSC-2725-x-AH
				4	5-3/64	4-1/8	5-3/16	12	6	3/4	144	FTSC-2796-x-AH
				6	7-3/64	6-1/4	5-3/16	12	6	3/4	152	FTSC-2884-x-AH
				8	9-3/64	8-1/4	5-3/16	16	8	3/4	220	
				10	11-3/64	10-1/4	5-3/16	20	10	3/4	262	
				12	13-3/64	12-1/4	5-3/16	24	12	3/4	330	
				14	15-5/16	13-1/2	6-1/4	28	14	3/4	420	
				16	17-5/16	15-1/2	6-1/4	32	16	3/4	495	
				18	19-17/32	17-1/2	6-1/4	36	18	3/4	550	
30"	29.78-30.48 30.48-31.18 31.52-32.22			20	21-17/32	19-1/2	6-1/4	40	20	3/4	610	
				24	25-17/32	23-1/2	6-1/4	48	24	3/4	740	
				2	3-3/64	2-1/16	5-3/16	12	6	3/4	160	**FTSC-3048-x-AH
				3	4-3/64	3-1/16	5-3/16	12	6	3/4	162	
				4	5-3/64	4-1/8	5-3/16	12	6	3/4	162	
				6	7-3/64	6-1/4	5-3/16	12	6	3/4	168	
				8	9-3/64	8-1/4	5-3/16	16	8	3/4	222	**FTSC-3118-x-AH
				10	11-3/64	10-1/4	5-3/16	20	10	3/4	283	
				12	13-3/64	12-1/4	5-3/16	24	12	3/4	350	FTSC-3222-x-AH
				14	15-5/16	13-1/2	6-1/4	28	14	3/4	520	
				16	17-5/16	15-1/2	6-1/4	32	16	3/4	550	
				18	19-17/32	17-1/2	6-1/4	36	18	3/4	580	
				20	21-17/32	19-1/2	6-1/4	40	20	3/4	682	
				24	25-17/32	23-1/2	6-1/4	48	24	3/4	832	
				30	31-1/16	29-9/16	6-1/4	60	30	3/4	981	

*To Order: Add flange size code to the sleeve number. Example: A 12" flange on 24" cast iron pipe would be FTSC-2641-12-AH.

** Size on size for this range is not available.

Note: A 1" undersize cutter is required for flanges 14" and larger. Oversize outlets are available by special request.

FEATURES

- Heavy welded steel meeting ASTM A36 36,000 psi minimum yield
- Bolts and nuts are made of high strength, low alloy steel per ASTM A242 and AWWA C111
- Ring style gasket is NBR (Buna-N) per ASTM D2000
- Finish is fusion-bonded epoxy coating
- Certified to ANSI/NSF 61 approved
- Rated for 250 psi up to 24" outlets. 30"-36" outlets rated for 200 psi. Ratings not to exceed the rating of the pipe.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

03/29/22

Submitted By: