



SUBMITTAL INFORMATION

Steel Tapping Sleeve - (FTSC-xxxx-xx-MJ-U style)



STEEL TAPPING SLEEVE - EPOXY COATED WITH 304 STAINLESS HARDWARE - 16" TO 30" WITH MECHANICAL JOINT OUTLET



NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	BY	OUTLET SIZE CODE*	NOMINAL DIMENSIONS - INCHES			MIN. NO. OF BOLTS	APPROX. WT. LBS.	CATALOG NUMBER*	✓ SUBMITTED ITEM(S)
				A	B	C				
16"-18"	17.33-17.87		4	4-1/4	5-3/16	12	6	105	FTSC-1787-xx-MJ-U	
	17.88-18.43		6	6-13/32	5-3/16	12	6	116	**FTSC-1843-xx-MJ-U	
	18.46-19.03		8	8-13/32	5-3/16	16	8	162	**FTSC-1903-xx-MJ-U	
	18.87-19.45		10	10-27/64	5-3/16	20	10	215	FTSC-1945-xx-MJ-U	
	19.41-20.01		12	12-27/64	5-3/16	24	12	240	FTSC-2001-xx-MJ-U	
			16	16	6-1/4	32	16	270		
18"-20"	19.88-20.48		4	4-1/4	5-3/16	12	6	120	FTSC-2048-xx-MJ-U	
	20.29-20.92		6	6-13/32	5-3/16	12	6	135	FTSC-2092-xx-MJ-U	
	20.93-21.57		8	8-13/32	5-3/16	16	8	185	FTSC-2157-xx-MJ-U	
	21.51-22.15		10	10-27/64	5-3/16	20	10	240	FTSC-2215-xx-MJ-U	
	22.16-22.81		12	12-27/64	5-3/16	24	12	270	FTSC-2281-xx-MJ-U	
			16	16	6-1/4	32	16	300		
20"-24"	22.78-23.45		4	4-1/4	5-3/16	12	6	131	FTSC-2345-xx-MJ-U	
	23.46-24.16		6	6-13/32	5-3/16	12	6	142	FTSC-2416-xx-MJ-U	
	24.15-24.85		8	8-13/32	5-3/16	16	8	196	FTSC-2485-xx-MJ-U	
	24.82-25.52		10	10-27/64	5-3/16	20	10	257	FTSC-2552-xx-MJ-U	
			12	12-27/64	5-3/16	24	12	283		
			16	16	6-1/4	32	16	313		
24"	25.71-26.41		4	4-1/4	5-3/16	12	6	147	FTSC-2641-xx-MJ-U	
	26.55-27.25		6	6-13/32	5-3/16	12	6	155	FTSC-2725-xx-MJ-U	
	27.26-27.96		8	8-13/32	5-3/16	16	8	217	FTSC-2796-xx-MJ-U	
	28.14-28.84		10	10-27/64	5-3/16	20	10	284	FTSC-2884-xx-MJ-U	
			12	12-27/64	5-3/16	24	12	300		
			16	16	6-1/4	32	16	330		
30"	29.78-30.48		4	4-1/4	5-3/16	12	6	152	FTSC-3048-xx-MJ-U	
	30.48-31.18		6	6-13/32	5-3/16	12	6	160	FTSC-3118-xx-MJ-U	
	31.52-32.22		8	8-13/32	5-3/16	16	8	222	FTSC-3222-xx-MJ-U	
			10	10-27/64	5-3/16	20	10	290		
			12	12-27/64	5-3/16	24	12	308		
			16	16	6-1/4	32	16	338		

*To Order: Add outlet size code to the sleeve number. Example: A 12" outlet on 24" cast iron pipe would be FTSC-2641-12-MJ-U.

** Size on size for this range is not available.

Note: A 1" undersize cutter is required for outlets 14" and larger. Oversize outlets are available by special request.

FEATURES

- Heavy welded steel meeting ASTM A36 36,000 psi minimum yield
- Bolts and nuts are made of type 304 stainless steel per ASTM A193 and A194
- Fusion-bonded epoxy-coating on body
- Certified to ANSI/NSF 61
- Rated for up to 250 psi. Rating not to exceed the pressure rating of the pipe.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

08/08/22

Submitted By: