


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve - (FTSS-xxx-TAP style)



4"-12" TYPE 304 STAINLESS STEEL TAPPING SLEEVE WITH IP OR CC TAPPED OUTLET



Outlet Gasket - Gridded NBR (Buna-N) compounded for water service, per ASTM D2000. Outlet gasket ensures complete seal of outlet area.

Full Gasket - Gridded virgin SBR compounded for water service, per ASTM D2000. Full gasket gives 360° pipe coverage.

Armors - Heavy gauge type 304 stainless steel are vulcanized to gasket and recessed to bridge the gap between lugs.

3/16" lug (1/4" lug if using a 3/4" bolt)

CC or IP Tap per AWWA C800



Bolts, Nuts, & Washers - Type 304 stainless steel per ASTM A193 and A194. Heavy hex nuts and washers are coated to prevent galling and maximize bolt efficiency.

NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	CATALOG NUMBER	BOLT DIA.	MIN. NO. BOLTS	✓ SUBMITTED ITEM(S)
4"	4.50-4.80	FTSS-480-TAP	5/8"	8	
	4.80-5.00	FTSS-500-TAP			
	5.10-5.30	FTSS-530-TAP			
	5.20-5.40	FTSS-540-TAP			
6"	6.63-7.00	FTSS-700-TAP	5/8"	8	
	6.90-7.10	FTSS-710-TAP			
	7.10-7.30	FTSS-730-TAP			
	7.30-7.50	FTSS-750-TAP			
8"	8.63-9.05	FTSS-905-TAP	5/8"	8	
	9.05-9.30	FTSS-930-TAP			
	8.97-9.45	FTSS-945-TAP			
	9.30-9.60	FTSS-960-TAP			
10"	9.45-9.75	FTSS-975-TAP	5/8"	8	
	10.75-11.10	FTSS-1110-TAP			
	11.10-11.40	FTSS-1140-TAP			
	11.06-11.45	FTSS-1145-TAP			
12"	11.40-11.70	FTSS-1170-TAP	5/8"	8	
	11.85-12.15	FTSS-1215-TAP			
	12.75-13.20	FTSS-1320-TAP			
	13.20-13.50	FTSS-1350-TAP			
	13.12-13.52	FTSS-1352-TAP			
	13.50-13.80	FTSS-1380-TAP			
	14.10-14.40	FTSS-1440-TAP			

OUTLET TAP CODE

CC (AWWA) THREAD		
THREAD	CODE NUMBER	✓ SUBMITTED ITEM(S)
1/2" CC	CC1	
3/4" CC	CC3	
1" CC	CC4	
1-1/4" CC	***CC5	
1-1/2" CC	CC6	
2" CC	CC7	

IP THREAD		
THREAD	CODE NUMBER	✓ SUBMITTED ITEM(S)
3/4" IP	IP3	
1" IP	IP4	
1-1/4" IP	***IP5	
1-1/2" IP	IP6	
2" IP	IP7	
3" IP	IP9	
4" IP	IP11	

*** Contact factory for availability

* To order: Add outlet tap code to catalog number. Example: The complete FTSS catalog number for a 6" pipe (6.90 O.D.) with a 3/4" CC tap is FTSS-710-CC3.

FEATURES

- Body, straps and UNC threaded bolts are made of 304 stainless steel.
- All welds are fully passivated for corrosion resistance.
- Outlet gasket is NBR (Buna-N) rubber per ASTM D2000
- Rated for the lesser of pressure rating of the pipe or 250 psi

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

10/18/22

Submitted By: