



SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve - (FTSS-xxxx-xx style)



TAPPING SLEEVE WITH STAINLESS STEEL OR CARBON STEEL FLANGE



NOM. PIPE SIZE (IN.)	SLEEVE O.D. RANGE (IN.)	CATALOG NUMBER	FLANGED OUTLET SIZE (IN.)	NOMINAL DIMENSIONS - INCHES				MIN. No. BOLTS	BOLT DIA. (IN.)	APPROX. WT. (LBS.)	✓ SUBMITTED ITEM(S)
				COUNTER-BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH				
				A	B	C	D				
20	20.20-20.60 20.90-21.30 21.20-21.60 21.40-21.80 21.86-22.26 22.30-22.70 23.40-23.80	FTSS-2060-xx FTSS-2130-xx FTSS-2160-xx FTSS-2180-xx FTSS-2226-xx FTSS-2270-xx FTSS-2380-xx	2	3-1/16	3-1/4	5-3/8	16	10	3/4	84	
			3	4-1/16	3-1/4	4-15/16	16	10	3/4	85	
			4	5-1/16	4-1/4	4-15/16	16	10	3/4	86	
			6	7-1/16	6-13/32	5-1/4	16	10	3/4	92	
			8	9-1/16	8-13/32	5-3/8	20	14	3/4	114	
			10	11-1/16	10-15/32	5-7/8	20	14	3/4	123	
			12	13-1/16	12-13/32	6	24	16	3/4	162	
			14	15-9/32	13-1/2	6-1/8	24	16	3/4	195	
			16	17-9/32	15-1/2	6-1/8	32	20	3/4	205	
			18	19-1/2	17-1/2	6-1/8	36	24	3/4	215	
24	23.80-24.20 25.60-26.00 26.01-26.41 26.20-26.60	FTSS-2420-xx FTSS-2600-xx FTSS-2641-xx FTSS-2660-xx	2	3-1/16	3-1/4	5-3/8	16	10	3/4	95	
			3	4-1/16	3-1/4	4-15/16	16	10	3/4	96	
			4	5-1/16	4-1/4	4-15/16	16	10	3/4	97	
			6	7-1/16	6-13/32	5-1/4	16	10	3/4	103	
			8	9-1/16	8-13/32	5-3/8	20	14	3/4	127	
			10	11-1/16	10-15/32	5-7/8	20	14	3/4	136	
			12	13-1/16	12-13/32	6	24	16	3/4	178	
			14	15-9/32	13-1/2	6-1/8	24	16	3/4	199	
			16	17-9/32	15-1/2	6-1/8	32	20	3/4	210	
			18	19-1/2	17-1/2	6-1/8	36	24	3/4	224	
24	26.01-26.41 26.20-26.60	FTSS-2641-xx FTSS-2660-xx	20	21-1/2	19-1/2	6-1/8	40	24	3/4	230	
			24	25-1/2	23-1/2	6-1/8	48	28	3/4	256	

* The complete FTSS catalog number for a 20" pipe (21.80 O.D.) with a 16" stainless steel flange is FTSS-2180-16. For carbon steel flange, add "A" to the catalog number. Example: FTSS-2180-16A.

Note: A 1" undersize cutter is required for flanges 14" and larger. Oversize outlets are available by special request.

Note: Highlighted ranges are recommended for ductile iron pipe, pit cast and C900/C905 pipe applications.

FEATURES

- Body, straps and UNC threaded bolts are made of type 304 stainless steel. Flange can be either type 304 stainless steel or ASTM A36 carbon steel. All welds are fully passivated for corrosion resistance
- Certified to ANSI/NSF 61
- Complies with AWWA C223 and MSS SP-124
- 14"-16" rated to 200 psi. 18"-20" rated to 175 psi. 24" rated to 150 psi. Rating not to exceed the pressure rating of the pipe.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

04/25/25

Submitted By: