


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve 30"-36" - (FTSSP-xxxx-xx style)





TAPPING SLEEVE WITH STAINLESS STEEL OR CARBON STEEL FLANGE FOR HDPE PIPE

Flange - Type 304 stainless steel with recess per MSS SP60 to accept standard tapping valves. Flange conforms to AWWA C228 Class D ANSI 150# drilling. Optional carbon steel flange, per AWWA C207, is available.

Bolts, Nuts, & Washers - Type 304 stainless steel per ASTM A193 and A194. Heavy hex nuts are coated to prevent galling and maximize bolt efficiency.

Washers - Belleville Spring Washer 17-7 PH Stainless Steel. Quantity may vary.

Outlet Pipe - Type 304 stainless steel.



Outlet Gasket - Virgin NBR (Buna-N) compounded for water service, per ASTM D2000. Outlet gasket ensures complete seal of outlet area.

Full Gasket - Gridded virgin SBR compounded for water service, per ASTM D2000. Full gasket gives 360° pipe coverage.

Armors - Hardened heavy gauge stainless steel are vulcanized to gasket and recessed to bridge the gap between lugs.

NOM. PIPE SIZE	SLEEVE O.D. RANGE (IN.)	CATALOG NUMBER	FLANGED OUTLET SIZE	NOMINAL DIMENSIONS - INCHES				MIN. No. BOLTS	BOLT DIA.	APPROX. WT. (LBS.)	✓SUBMITTED ITEM(S)
				COUNTER-BORE ID	OUTLET PIPE ID	TOP OF PIPE TO TOP OF FLANGE	WIDTH				
				A	B	C	D				
30"	30.00 32.00	FTSSP-3000-xx FTSSP-3200-xx	2	3-1/16	3-1/4	5-1/16	16	10	3/4"	211	
			3	4-1/16	3-1/4	5-1/16	16	10	3/4"	212	
			4	5-1/16	4-1/4	5-1/16	16	10	3/4"	254	
			6	7-1/16	6-13/32	5-1/16	16	10	3/4"	192	
			8	9-1/16	8-13/32	5-1/16	20	14	3/4"	209	
			10	11-1/16	10-15/32	5-1/16	20	14	3/4"	274	
			12	13-1/16	12-13/32	5-1/16	24	16	3/4"	344	
			14	15-9/32	13-1/2	6-1/8	24	16	3/4"	418	
			16	17-9/32	15-1/2	6-1/8	32	20	3/4"	492	
			18	19-1/2	17-1/2	6-1/8	36	24	3/4"	552	
			20	21-1/2	19-1/2	6-1/8	40	24	3/4"	623	
			24	25-1/2	23-1/2	6-1/8	48	28	3/4"	747	
36"	36.00 38.30	FTSSP-3600-xx FTSSP-3830-xx	2	3-1/16	3-1/4	5-1/16	16	10	3/4"	253	
			3	4-1/16	3-1/4	5-1/16	16	10	3/4"	254	
			4	5-1/16	4-1/4	5-1/16	16	10	3/4"	256	
			6	7-1/16	6-13/32	5-1/16	16	10	3/4"	260	
			8	9-1/16	8-13/32	5-1/16	20	14	3/4"	266	
			10	11-1/16	10-15/32	5-1/16	20	14	3/4"	315	
			12	13-1/16	12-13/32	5-1/16	24	16	3/4"	397	
			14	15-9/32	13-1/2	6-1/8	24	16	3/4"	472	
			16	17-9/32	15-1/2	6-1/8	32	20	3/4"	507	
			18	19-1/2	17-1/2	6-1/8	36	24	3/4"	630	
			20	21-1/2	19-1/2	6-1/8	40	24	3/4"	735	
			24	25-1/2	23-1/2	6-1/8	48	28	3/4"	836	
			30	31-1/16	29-9/16	6-1/4	60	36	3/4"	1033	

* For carbon steel flange, add "A" to the catalog number. Example: The complete FTSSP catalog number for a 30" pipe (30.00 O.D.) with a 12" stainless steel flange is FTSSP-3000-12. For a carbon steel flange the number is FTSSP-3000-12A. Add "-SP" for stainless steel test plug.

Note: A 1" undersize cutter is required for flanges 14" and larger. Oversize outlets are available by special request.

FEATURES

- Body, straps and UNC threaded bolts are made of type 304 stainless steel. Flange can be either type 304 stainless steel or ASTM A36 carbon steel. All welds are fully passivated for corrosion resistance.
- Outlet gasket is NBR (Buna-N) per ASTM D2000.
- Other sizes and ranges available. Contact your Ford Meter Box® representative for details.
- Removable bolts

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

03/07/23

Submitted By: