


SUBMITTAL INFORMATION

Angle Key Flange Meter Valves - (FV63-666W-IDR7-AWT-NL style)



PACK JOINT FOR POLYETHYLENE PIPE (SIDR7 PEP) INLET BY METER FLANGE OUTLET, ASSEMBLED WATERTIGHT



VALVE SIZE	SERVICE LINE SIZE INLET	METER SIZE OUTLET	LENGTH	HEIGHT	APPROX. Wt. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
1-1/2"	1-1/2"	1-1/2"	1-7/32"	6"	8.8	FV63-666W-IDR7-AWT-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Padlock wing for locking valve in closed position
- Flat drop-in gaskets included
- Ends are integral or secured with adhesive to prevent unintentional disassembly
- Meets 80 PSI working pressure requirements of AWWA Standard C800

Optional Meter Support Brackets. Add "-MSB" to end of part number

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

06/03/20

Submitted By: