

## SUBMITTAL INFORMATION





BALL VALVE INLET BY ANGLE CASCADING DUAL CHECK VALVE OUTLET (5/8", 5/8"x3/4", OR 3/4" METER) WITHOUT SERVICE LINE CONNECTIONS



METER SIZE	METER	APPROX.	APPROX.	COPPER	Body	APPROX.	CATALOG	✓ SUBMITTED
	SPACING	LENGTH	WIDTH	TUBE O.D.	THREADS	Wt. Lbs.	Number	ITEM(S)
5/8"	7-1/2"	4-1/2"	11-1/8"	13/16"	3/4" Kornerhorn	4.1	KHVBHH-1-NL	
5/8"x3/4"	7-1/2"	4-1/2"	11-1/8"	13/16"	3/4" Kornerhorn	4.3	KHVBHH-2-NL	
3/4"	9"	4-1/2"	12-5/8"	15/16"	3/4" Kornerhorn	4.3	KHVBHH-3-NL	

## **FEATURES**

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Copper conforms to ASTM B75 or B88, UNS C12200
- All Ford<sup>®</sup> Setters are assembled with lead-free solder
- Kornerhorns ensure proper spacing and orientation for meters
- Permanent electrical bonding is provided without straps
- Copper tubing with full diameter bends provides excellent flow capacity
- Two Pack Joint assemblies required to connect to service line order separately
- ASSE 1024 approved dual check valve

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



## The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overes as Few 900 F02 0407

Overseas Fax: 260-563-0167 www.fordmeterbox.com

12/21/22

_	-			
Q,	ıhr	nitte	- M	R٧