

SUBMITTAL INFORMATION

Swivel Quarter Bend - (L04-xxS-TW-Q-NL style)



FEMALE COPPER THREAD SWIVEL NUT INLET BY QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS) OUTLET WITH TRACER WIRE OPTION



Due to design variations related to sizing, items may differ from images above.

DESCRIPTION (IN.)		LENGTH	HEIGHT	APPROX.	Part	✓ SUBMITTED
FEMALE COPPER	Q.J. FOR CTS	(ln.)	(ln.)	Wt. Lbs	Number	ITEM(S)
3/4	3/4	1-13/16	1-3/4	1.2	L04-33S-TW-Q-NL	
1	1	2	2-1/8	1.9	L04-44S-TW-Q-NL	
1-1/2	1-1/2	3	3	3.8	L04-66S-TW-Q-NL	
2	2	3-1/8	3-3/8	6.9	L04-77S-TW-Q-NL	

Note: Ford recommends insert stiffeners when using plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Fits F600, F700 corporation stops (3/4" & 1") and FB600, FB700 ballcorps
- Swivel nut inlet allows proper outlet positioning without compromising installation torque
- Copper gasket included to ensure proper inlet seal

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

09/20/24

Submitted By: