



SUBMITTAL INFORMATION

Angle Meter Coupling - (L34-xx-U-AWT-NL style)



METER SWIVEL NUT BY ULTRA-TITE FOR COPPER OR PLASTIC TUBING (CTS), ASSEMBLED WATERTIGHT



DESCRIPTION		ULTRA-TITE OUTLET O.D. RANGE (INCHES)	LENGTH	HEIGHT	APPROX. WT. LBS.	PART NUMBER	✓ SUBMITTED ITEMS
METER SIZE	ULTRA-TITE FOR CTS						
5/8"x3/4" & 3/4"	3/4"	0.871 - 0.879	1-19/32"	3-23/32"	1.0	L34-23-U-AWT-NL	
1"	1"	1.120 - 1.130	2-1/8"	4-15/64"	2.0	L34-44-U-AWT-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Conforms to AWWA C700 for meter threads.
- Body design provides wrench flats to facilitate installation.
- Ends are integral or secured with adhesive to prevent unintentional disassembly

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

05/01/19

Submitted By: