




SUBMITTAL INFORMATION

Yoke Ell Couplings - (L94-xxD-Q-NL style)



METER YOKE NOSE BY QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS)



Due to design variations related to sizing, items may differ from images above.

METER SIZE	QUICK JOINT SIZE	LENGTH (IN.)	HEIGHT (IN.)	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
5/8"	3/4"	1-1/2	1-7/8	1.0	*L94-13D-Q-NL	
5/8"x3/4"&3/4"	3/4"	1-1/2	1-7/8	1.0	*L94-23D-Q-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

*Drain/Test valve on top (not on side of fitting) - Add "TD" to catalog number

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Body design provides larger, more rugged wrench flats for proper installation
- Yoke ell couplings may be used on either end of the yoke
- EPDM rubber yoke nose gasket sold separately: GT-112 (5/8"), GT-118 (3/4") and GT-123 (1")

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
 Phone: 260-563-3171 / Fax: 800-826-3487
 Overseas Fax: 260-563-0167
www.fordmeterbox.com

Submitted By: