



# SUBMITTAL INFORMATION

## Long Yokebox - (LYLBP141-233-REC-T-G-NL style)



GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY FEMALE IRON PIPE THREAD OUTLET

STRAIGHT BALL VALVE BY STRAIGHT DUAL CARTRIDGE CHECK VALVE



| METER SIZE  | CTS PJ INLET | FIP OUTLET | APPROX. WT. LBS. | CATALOG NUMBER          | ✓ SUBMITTED ITEM(S) |
|-------------|--------------|------------|------------------|-------------------------|---------------------|
| 5/8" x 3/4" | 3/4"         | 3/4"       | 30.6             | LYLBP141-233-REC-T-G-NL |                     |

**Note:** Ford recommends using insert stiffeners with plastic pipe or tubing

### FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Base and lid are cast iron per ASTM A48, Class 25 with black e-coat finish
- Polyethylene upper section
- The dual cartridge check valve is ASSE 1024 approved
- The brass end fittings are permanently and properly spaced and aligned for the meter
- Locking lid with 2" hole and recession for electronic meter reading module
- Optional: Lockless lid available by adding "-LL" to the part number

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
 Phone: 260-563-3171 / Fax: 800-826-3487  
 Overseas Fax: 260-563-0167  
[www.fordmeterbox.com](http://www.fordmeterbox.com)

Submitted By: