

SUBMITTAL INFORMATION





DOUBLE PURPOSE INLET BY FEMALE IRON PIPE THREAD OUTLET

STRAIGHT KEY VALVE BY STRAIGHT DUAL CARTRIDGE CHECK VALVE



METER	*Double	FIP	APPROX.	CATALOG	✓ SUBMITTED
Size	PURPOSE INLET	OUTLET	WT. LBS.	Number	ITEM(S)
5/8" x 3/4"	3/4"	3/4"	28.4	LYLVP111-233-TP-NL	

^{*} Double Purpose Unions will accommodate male iron pipe threads or flare copper.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Base and lid are cast iron per ASTM A48, Class 25 with black e-coat finish
- Polyethylene upper section
- The dual cartridge check valve is ASSE 1024 approved
- The brass end fittings are permanently and properly spaced and aligned for the meter
- Lockless lid is available. Add "-LL" to catalog number

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

06/20/14

_			
Sı.	ıhr	nitte	dRv